



- All versions feature red 'mains-on' neon indicator
- Shuttered outlets
- Manufactured to **BS1363A**

*Fused at mains plug, all other options fused at distribution board

	Fuse	Switch	Mains Lead and Plug	Remov-able Terminal Cover	Wall Mount-able	Dimensions H W D	Mfrs. List No.
Fused	13A	-	-	-	Yes	31 315 67	FC4134B
Switched	-	Yes	-	Yes	Yes	31 315 67	FC4135B
Switched and fused	13A	Yes	-	Yes	Yes	31 315 67	FC4136B
Switched and 2m lead	*13A	Yes	-	-	-	31 315 67	EXL136
1m lead	*13A	-	Yes	Yes	-	29 130 105	EXL4133W
Total current rating	13A@250Vac		Cover	FC4134			
Max load	3120W		Contacts	FC4135/6, 107-607ABS Polycarbonate Solid brass			

219689

Colour	Mfrs. List No.	Order Code	1+	5+	10+	25+
Unswitched and Fused without Lead						
Black	FC4134 BLK	313-592	831.00	775.00	744.00	702.00
White	FC4134WHI	313-609	906.00	860.00	815.00	770.00
Switched without Lead						
Black	FC4135BLK	313-610	1,049.00	996.00	944.00	891.00
White	FC4135WHI	313-622	1,137.00	1,038.00	1,025.00	967.00
Switched and Fused without Lead						
Black	FC4136 BLK	313-634	1,222.00	1,161.00	1,102.00	1,040.00
White	FC4136WHI	313-646	1,268.00	1,198.00	1,143.00	1,080.00
Switched with Fused Plug and 2m Lead						
Black	EXL136BLK	313-658 ◊	1,688.00	1,604.00	1,535.00	1,491.00
White	EXL136WHI	313-660 ◊	1,688.00	1,604.00	1,535.00	1,491.00

◊ Fits UK 3 Pin Mains Socket

6 Way Individually Switched 20A



H=53, W=527, D=89, Plug and cable not included

- Fitted with 6 switched 13A outlet sockets to **BS1363A: 1984**
- Red 'mains-on' neon indicator
- All insulated corrosion resistant base, earth bonded for maximum security

Total current rating	13A socket 20A max @ 250Vac	Housing	Blue, glass reinforced polyester case Single socket polycarbonate/ABS
Max. load	4600W		
Mfrs. List No.		DB613/SW	

209038

Order Code	1+	5+	10+	25+	+
143-601	4,528.00	4,302.00	4,189.00	3,929.00	--

Stripbloc™ 5 and 6 Way IEC



- A range of European moat plug with multi-way outlets
- Black ABS moulding, incorporating **IEC320** components
- IEC320 components approvals: **BEAB/BSI, UL, CSA** and **VDE**
- Common housing for 5 and 6 way
- 5 way unit has red 'mains-on' neon indicator
- Panel mount version has 6.35mm push-on tabs

Trailing/wall mounted
5 and 6 way - 2m lead and plug
H=40, W=228, D=59
Fixing centres=200 x 44, 3.2 diaP

Current rating	6A @250Vac (fused) 10A @250Vac (non-fused)	Housing	Black ABS
Fuse (where fitted)	6.3A, 20x5 mm	Outlets	Black noryl, UL94V-0
Temperature range	-5°C to 60°C	Contacts	Brass, Nickel plated
Mfrs. List No.	R47404300=561-101 R47404300=561-101 R47404300=561-101	R47406000=269-190	R47403000=147-722
		R47404300=561-095	R47403600=439-277

219693

Order Code	Price Each			
	1+	50+	100+	250+
6 outlets				
150-631	1,436.00	1,228.00	1,025.00	914.00
IEC Inlet				
5 outlets & illum. Switch				
269-190	2,239.00	1,914.00	1,598.00	1,426.00
5 outlets, neon & fuse				
147-722	2,438.00	2,085.00	1,740.00	1,461.00
2m Mains Lead				
5 outlets, neon & fuse & 13A plug				
150-632 ◊	2,317.00	2,086.00	2,030.00	1,852.00
5 outlets, neon, fuse & 90° schuko plug				
439-277 ◊	2,263.00	2,044.00	1,824.00	1,702.00
6 outlets & 13A plug				
561-095 ◊	2,289.00	1,817.00	1,589.00	1,422.00
6 outlets & 90 schuko plug				
561-101 ◊	2,070.00	1,842.00	1,508.00	1,367.00

◊ Fits UK 3 Pin Main Socket

'Quadbox' 4 way IEC



- Compact distribution module
- 4 IEC 320 Class I unshuttered outlets
- Surface mounting
- Uses separate cordset, worldwide market appeal
- Available in black or white
- Approvals, **UL & CSA**

H=37, W=147, D=44

Contact rating	10A @ 250Vac	Housing	Polyamide 6	UL94V-0
Temperature range	-20°C to 70°C	Contacts		Brass, Tin plated
Mfrs. List No.	47470000=112-5809	47470010=964-499		

219735

Colour	Order Code	Price Each			
		1+	50+	100+	250+
Black	112-5809 ●	960.00	821.00	685.00	575.00

Mains Extension Leads

Cable Reels



- Made in England
- Fitted with twin sockets
- Overload reset fitted on selected models
- All models conform to **BS5733, BS6500, BS4343**

7

Connectors - Power & Mains

Compliant
Non-compliant
+ Limited stock - RoHS replacement available
RoHS