

**Cable Harnessing & Accessories**

**Cable Ties**



- One piece non-releasable cable ties manufactured in Natural or Black Nylon 66
- Flame retardant to **UL94V-2**

Operating temperature -40°C to +85°C

Length	Width	Min. Tensile Strength (kg)	Max. Bundle Dia.	Natural Order Code	Black Order Code
102	2.5	8.1	25	268-495	268-598
200	2.5	8.1	50	268-501	268-604
140	3.6	18.2	30	268-513	268-616
200	3.6	18.2	75	268-525	268-628
120	4.8	22.2	24	268-537	268-630
200	4.8	22.2	50	268-549	268-641
250	4.8	22.2	75	268-550	268-653
370	4.8	22.2	100	268-562	268-665
200	7.6	54.5	50	268-574	268-677
375	7.6	54.5	105	268-586	268-689

208013

100 Per Pack	Order Code	Price Per Pack				
		1+	5+	10+	25+	
Natural	268-495	127.00	114.00	66.00	55.00	
	268-501	188.00	164.00	137.00	115.00	
	268-513	175.00	159.00	130.00	84.00	
	268-525	230.00	214.00	177.00	148.00	
	268-537	205.00	183.00	154.00	131.00	
	268-549	246.00	233.00	188.00	159.00	
	268-550	510.00	447.00	382.00	313.00	
	268-562	547.00	527.00	410.00	336.00	
	268-574	703.00	615.00	526.00	434.00	
	268-586	775.00	746.00	646.00	513.00	
	Black	268-598	131.00	115.00	98.00	78.00
		268-604	188.00	164.00	137.00	115.00
268-616		193.00	170.00	143.00	120.00	
268-628		428.00	357.00	302.00	251.00	
268-630		205.00	183.00	154.00	131.00	
268-641		311.00	274.00	227.00	188.00	
268-653		510.00	447.00	382.00	313.00	
268-665		646.00	567.00	479.00	396.00	
268-677		703.00	615.00	526.00	434.00	
268-689		1,037.00	912.00	775.00	638.00	

**Releasable Cable Ties**



- One piece releasable cable ties manufactured in Natural or Black Nylon 66
- Flame retardant to **UL94V-2**
- Ideally suited for servicing/replacement or prototyping work


Operating temperature -40°C to +85°C

Length	Width	Min. Tensile Strength (kg)	Max. Bundle Dia.	Natural Order Code	Black Order Code
125	7.6	22	30	121-8017	434-050
150	8	22	35	434-024	434-061
200	8	22	50	434-036	434-073
300	8	22	80	434-048	434-085

208054

100 Per Pack	L	W	Max. Dia.	Order Code	Price Per Pack			
					1+	5+	10+	50+
Natural	125	7.6	30	121-8017	309.00	272.00	230.00	192.00
	150	8	35	434-024	389.00	340.00	290.00	248.00
	200	8	50	434-036	455.00	399.00	341.00	285.00
	300	8	80	434-048	744.00	652.00	554.00	457.00
Black	125	7.6	30	434-050	309.00	272.00	230.00	192.00
	150	8	35	434-061	389.00	340.00	290.00	248.00
	200	8	50	434-073	455.00	399.00	341.00	285.00
	300	8	80	434-085	744.00	652.00	554.00	457.00

**Cable Tie Mounting Bases**



- Natural or Black ABS plastic mounting bases with self-adhesive or central screw fixing options
- Accepts ties from all four sides


Operating temperature -15°C to +75°C

Base Size	Max. Cable Tie Width	Central Hole Dia.	Natural Order Code	Black Order Code
19 x 19	3.6	4.3	268-690	268-719
25 x 25	4.8	4.3	268-707	268-720

20812

100 Per Pack	Order Code	Price Per Pack			
		1+	5+	10+	50+
Natural	268-690	469.00	419.00	355.00	296.00
	268-707	555.00	490.00	419.00	324.00
Black	268-719	469.00	419.00	355.00	296.00
	268-720	555.00	490.00	419.00	352.00

**Cable Tie Mounting Bases**



- Natural or Black nylon 66 mounting bases, self-adhesive or central screw fixing
- Accepts ties from all four sides
- Flame retardant to **UL94V2**

Base size=28 x 28, Max. cable width=5, Mounting hole=5

208167

100 Per Pack	Order Code	Price Per Pack			
		1+	5+	10+	50+
Natural	121-8024	514.00	453.00	387.00	326.00
Black	121-8026	593.00	522.00	446.00	383.00

**'Heavy Duty' Ties**



- One piece non-releasable **BS EN ISO 9002** approved cable ties moulded in Nylon 66
- Flame retardant to **UL94V-2**. 'T' series manufactured to **US Mil. Spec.23190 Drwg.3367**.

Mfrs. List No.	Length	Width	Maximum Bundle Dia.	Tensile Strength (lbs)	(kg)
LK2A+ Colour	270	4.8	73	50	22.7
LK5+ Colour	540	13	152	250	113.4
T150M+ Colour	540	8.9	150	150	68
T250X+ Colour	370	12.5	100	250	113.4

208069

100 Per Pack	Mfrs. List No.	Colour	Order Code	Price Per Pack				
				1+	5+	10+	25+	+
LK2A-NAT	Natural	116-8955	686.00	643.00	574.00	490.00	--	
LK2A-BLACK	Black	116-8980	686.00	643.00	574.00	490.00	--	
LK5-NAT	Natural	116-9097	2,398.00	2,289.00	2,158.00	1,865.00	--	
LK5-BLK	Black	116-9098	2,398.00	2,289.00	2,158.00	1,865.00	--	
T150M-NAT	Natural	116-9100	2,238.00	2,097.00	1,976.00	1,709.00	--	
T150M-BLK	Black	116-9101	2,281.00	2,176.00	2,051.00	1,774.00	--	
T250X-BLK	Black	116-9102	2,359.00	2,249.00	2,120.00	1,832.00	--	

**Weather Resistant Cable Ties**



- One-piece non-releasable ties moulded in Black Nylon 66
- Flame retardant to **UL94V-2**
- UV stabilised

Operating temperature -40°C to +85°C (+105°C for short periods)

Mfrs. List No.	Length	Width	Maximum Bundle Dia.	Tensile Strength (lbs)	(kg)
T18I-W	145	2.5	36	18	8.1
T18R-W	100	2.5	22	18	8.1
T30L-W	200	3.5	49	30	13.6
T30R-W	130	3.5	35	30	13.6
T40R-W	180	4.0	42	40	18.1
T40L-W	260	3.3	65	40	18.1
T50S-W	150	4.6	36	50	22.7