

**Polyester Expandable Braided Sleeving**



- 0.22mm monofilament
- High flexibility
- High abrasion and good chemical resistance
- Self extinguishing

- Halogen free
- Passes flame resistance requirements to **CEI 332-1** and **FMVSS 302 (Type A) I2** according to **NF F 16-101**
- Available in Black and Grey
- Supplied on coils and reels

Operating temperature	-50°C to +150°C	Limiting oxygen index	34%
Nominal Dia.	Range of Use	Coil Length	Reel Length
10	7 to 15	100m	50m
12	8 to 17	50m	25m
15	10 to 21	50m	25m
25	18 to 32	25m	15m
30	20 to 40	25m	10m

208330.343056

Coils	Nom. Dia.	Coil Length	Order Code	Price Per Coil				
				1+	5+	10+	25+	+
Grey	5	100m	<b>322-3048</b>	3,016.00	2,613.00	2,323.00	1,790.00	--
	6	100m	<b>322-3050</b>	3,635.00	3,150.00	2,800.00	2,060.00	--
	8	100m	<b>322-3061</b>	4,147.00	3,592.00	3,193.00	2,349.00	--
	10	100m	<b>322-3073</b>	4,847.00	4,200.00	3,733.00	2,746.00	--
	12	50m	<b>322-3085</b>	2,827.00	2,450.00	2,177.00	1,601.00	--
	15	50m	<b>322-3097</b>	3,581.00	3,103.00	2,758.00	2,028.00	--
	20	25m	<b>322-3103</b>	2,074.00	1,796.00	1,597.00	1,175.00	--
Black	25	25m	<b>322-3115</b>	2,450.00	2,123.00	1,887.00	1,388.00	--
	30	25m	<b>322-3127</b>	3,029.00	2,625.00	2,333.00	1,716.00	--
	5	100m	<b>322-3139</b>	3,016.00	2,613.00	2,323.00	1,708.00	--
	6	100m	<b>322-3140</b>	3,635.00	3,150.00	2,800.00	2,060.00	--
	8	100m	<b>322-3152</b>	4,147.00	3,592.00	3,193.00	2,349.00	--
	10	100m	<b>322-3164</b>	4,847.00	4,200.00	3,733.00	2,746.00	--
	12	50m	<b>322-3176</b>	2,827.00	2,450.00	2,177.00	1,601.00	--
	15	50m	<b>322-3188</b>	2,800.00	2,686.00	--	--	--
	20	25m	<b>322-3190</b>	2,074.00	1,796.00	1,597.00	1,175.00	--
	25	25m	<b>322-3206</b>	2,450.00	2,123.00	1,887.00	1,388.00	--

**Price Per Reel**

Coils	Nom. Dia.	Coil Length	Order Code	Price Per Reel				
				1+	5+	10+	25+	+
Grey	5	50m	<b>322-3220</b>	1,640.00	1,421.00	1,263.00	929.00	--
	6	50m	<b>322-3231</b>	1,920.00	1,664.00	1,478.00	1,088.00	--
	8	50m	<b>322-3243</b>	2,365.00	2,048.00	1,821.00	1,340.00	--
	10	50m	<b>322-3255</b>	2,809.00	2,434.00	2,163.00	1,591.00	--
	12	25m	<b>322-3267</b>	1,656.00	1,435.00	1,276.00	938.00	--
	15	25m	<b>322-3279</b>	1,939.00	1,680.00	1,493.00	1,099.00	--
	20	25m	<b>322-3280</b>	1,910.00	1,655.00	1,470.00	1,082.00	--
Black	25	15m	<b>322-3292</b>	1,405.00	1,218.00	1,083.00	796.00	--
	30	10m	<b>322-3309</b>	1,395.00	1,209.00	1,075.00	790.00	--
	5	50m	<b>322-3310</b>	1,640.00	1,421.00	1,263.00	929.00	--
	6	50m	<b>322-3322</b>	1,920.00	1,664.00	1,478.00	1,088.00	--
	8	50m	<b>322-3334</b>	2,365.00	2,048.00	1,821.00	1,340.00	--
	10	50m	<b>322-3346</b>	2,809.00	2,434.00	2,163.00	1,591.00	--
	12	25m	<b>322-3358</b>	1,656.00	1,435.00	1,276.00	938.00	--
	15	25m	<b>322-3360</b>	1,939.00	1,680.00	1,493.00	1,099.00	--
	20	25m	<b>322-3371</b>	1,910.00	1,655.00	1,470.00	1,082.00	--
	25	15m	<b>322-3383</b>	1,405.00	1,218.00	1,083.00	796.00	--

**Medium Expansion Polyester Braided Sleeving**



- 0.22mm monofilament
- Medium expansion
- Imperial sizes
- High flexibility
- High abrasion and good chemical resistance

- Self-extinguishing
- Halogen free
- Passes flame resistant requirements of **CEI 332-1** and **FMVSS 302 (Type A) I2** according to **NF F 16-101**
- Supplied in Black on coils and reel

Operating temperature	-50°C to +150°C	Limiting oxygen index	34%
Nominal Dia.	Range of Use	Coil Length	Reel Length
¼" (6.4mm)	⅛" (3.2mm) to ⅜" (9.5mm)	100m	400m
⅜" (9.5mm)	⅜" (4.8mm) to ⅝" (15.8mm)	50m	300m
½" (12.7mm)	¼" (6.4mm) to ¾" (19.1mm)	50m	300m
¾" (19.1mm)	½" (12.7mm) to 1¼" (32mm)	25m	200m
1¼" (32mm)	¾" (19.1mm) to 1½" (38.2mm)	25m	200m

208329

Coils	Norm. Dia.	Coil Length	Order Code	Price Per Coil				
				1+	5+	10+	25+	+
100	¼" (6.4mm)	50	<b>322-3504</b>	4,463.00	3,316.00	2,652.00	2,210.00	--
100	⅜" (9.5mm)	50	<b>322-3516</b>	2,842.00	2,414.00	2,112.00	1,407.00	--
50	½" (12.7mm)	50	<b>322-3528</b>	4,323.00	3,668.00	3,210.00	2,140.00	--
25	¾" (19.1mm)	25	<b>322-3530</b>	3,304.00	2,805.00	2,454.00	1,636.00	--
25	1¼" (32mm)	25	<b>322-3541</b>	4,282.00	3,180.00	2,544.00	2,121.00	--

Reels	Norm. Dia.	Reel Length	Order Code	Price Per Reel				
				1+	5+	10+	25+	+
400	¼" (6.4mm)	400	<b>322-3553</b>	10,710.00	9,641.00	9,545.00	8,668.00	--
300	⅜" (9.5mm)	300	<b>322-3565</b>	11,377.00	10,139.00	9,217.00	8,287.00	--
300	½" (12.7mm)	300	<b>322-3577</b>	17,295.00	15,413.00	14,012.00	12,597.00	--
200	¾" (19.1mm)	200	<b>322-3589</b>	17,624.00	15,706.00	14,297.00	12,836.00	--
200	1¼" (32mm)	200	<b>322-3590</b>	20,701.00	18,634.00	18,149.00	16,711.00	--

**UL94-V0 PBT Medium Expansion Sleeving**



- 0.22mm monofilament
- Flame retardant to **UL94V-0**
- Medium expansion
- Imperial sizes
- High flexibility
- High abrasion and good chemical resistance

- Halogen free
- Passes flame resistance requirements of **ISO 3796** and **FMVSS 302**
- Complies with **CETDEC 26-0611**
- Supplied in Black with an identification stripe
- Supplied in coils

Operating temperature	-50°C to +150°C	Limiting oxygen index	34.7%
-----------------------	-----------------	-----------------------	-------

Nominal Dia.	Range Of Use	Coil Length
⅜" (9.5mm)	⅜" (4.8mm) to ⅝" (15.8mm)	50m
½" (12.7mm)	¼" (6.4mm) to ⅝" (19.1mm)	50m
¾" (19.1mm)	½" (12.7mm) to 1¼" (32mm)	25m
1¼" (32mm)	¾" (19.1mm) to 1½" (38.2mm)	25m

208328

Coils	Nom. Dia.	Coil Length	Order Code	Price Per Coil				
				1+	5+	10+	25+	+
100m	¼" (6.4)	100m	<b>322-3401</b>	5,267.00	4,564.00	4,056.00	2,984.00	--
50m	⅜" (9.5)	50m	<b>322-3413</b>	3,632.00	3,148.00	2,798.00	2,058.00	--
50m	½" (12.7)	50m	<b>322-3425</b>	5,154.00	4,466.00	3,970.00	2,920.00	--
25m	¾" (19.1)	25m	<b>322-3437</b>	4,209.00	3,647.00	3,241.00	2,385.00	--
25m	1¼" (32)	25m	<b>322-3449</b>	5,098.00	4,417.00	3,926.00	2,887.00	--

**High Expansion Polyester Braided Sleeving**



- 0.22mm monofilament
- High expansion
- Reduces inventory
- Easy installation over wire bundles
- Ideal for large termination or cable transitions
- High abrasion and good chemical resistance

- Self extinguishing
- Passes flame resistant requirements of **CEI 332-1** and **FMVSS 302 (Type A) I2** according to **NFF16-101**
- Available in Black
- Supplied in coils

Operating temperature	-50°C to +150°C	Limiting oxygen index	33%
-----------------------	-----------------	-----------------------	-----

208325

Coils	Nom. Range Dia. of Use	Coil Length	Order Code	Price Per Coil				
				1+	5+	10+	25+	+
100m	6 to 12	100m	<b>322-3607</b>	3,781.00	3,199.00	2,870.00	1,912.00	--
100m	12 to 21	100m	<b>322-3619</b>	5,666.00	4,799.00	4,209.00	3,135.00	--
100m	20 to 30	100m	<b>322-3620</b>	8,078.00	7,016.00	6,222.00	4,576.00	--
50m	30 to 60	50m	<b>322-3632</b>	5,856.00	5,000.00	4,375.00	2,916.00	--

**UL94V-0 Polyester Expandable Braided Sleeving**



- 0.22mm monofilament
- Flame retardant to **UL94V-0**
- High flexibility
- High abrasion and good chemical resistance
- Self-extinguishing
- Passes flame resistance requirements of **ISO 3795**, **FMVSS 302** and **FAR 25-853 I2** according to **NF F16-101 VO-UL94**
- Available in Black and Grey with identification stripes
- Supplies in coils

Operating temperature	-50°C to +150°C	Limiting oxygen index	34.7%
-----------------------	-----------------	-----------------------	-------

208327

Coils	Norm. Dia.	Range of Use	Coil Length	Order Code	Price Per Coil				
					1+	5+	10+	25+	+
100m	Grey	5 to 9	100m	<b>322-3644</b>	4,734.00	3,999.00	3,501.00	2,551.00	--
100m	6 to 11	100m	<b>322-3656</b>	5,698.00	4,798.00	4,209.00	2,961.00	--	
100m	8 to 13	100m	<b>322-3668</b>	6,059.00	5,249.00	4,698.00	3,433.00	--	
50m	10 to 15	50m	<b>322-3670</b>	4,017.00	3,399.00	2,975.00	1,983.00	--	
50m	12 to 17	50m	<b>322-3681</b>	4,952.00	4,226.00	3,675.00	2,450.00	--	
50m	15 to 20	50m	<b>322-3693</b>	6,157.00	5,000.00	4,375.00	2,916.00	--	