

Heat Shrink Tubing - continued

UL Marked 2:1 Shrink Ratio



- Black marked polyolefin heat shrink tubing
- Resistant to fuel, oils, hydraulic fluid
- Flame retardant to **VW-1, UL224, CSA C22.2**, manufactured to **MIL-DTL-23053/5**

Dielectric strength 25kV/mm min. Operating temperature -55°C to 135°C 219619

Dia.		Order Code	Price Per Length					
Nom.	Shrunk		1+	5+	10+	25+	+	+
Black - 1.2m Lengths								
1.2	0.6	119-0977	110.00	103.00	94.00	92.00	--	--
1.6	0.8	119-0978	153.00	--	--	--	--	--
2.4	1.2	119-0979	133.00	123.00	104.00	102.00	--	--
3.2	1.6	119-0980	138.00	130.00	113.00	108.00	--	--
4.8	2.4	119-0981	153.00	--	--	--	--	--
6.4	3.2	119-0983	168.00	160.00	153.00	--	--	--
9.5	4.7	119-0984	197.00	185.00	176.00	172.00	--	--
12.7	6.3	119-0985	244.00	232.00	209.00	205.00	--	--
19	9.5	119-0986	308.00	301.00	295.00	289.00	--	--
25.4	12.7	119-0987	482.00	469.00	456.00	447.00	--	--
Price Per Coil								
Black - 5m Coils								
1.2	0.6	119-0988	395.00	372.00	346.00	339.00	--	--
1.6	0.8	119-0989	414.00	391.00	365.00	357.00	--	--
2.4	1.2	119-0990	435.00	411.00	379.00	372.00	--	--
3.2	1.6	119-0991	440.00	421.00	396.00	387.00	--	--
4.8	2.4	119-0992	536.00	509.00	475.00	465.00	--	--
6.4	3.2	119-0993	630.00	590.00	552.00	516.00	--	--
9.5	4.7	119-0995	676.00	634.00	586.00	548.00	--	--
12.7	6.3	119-0996	569.00	538.00	520.00	476.00	--	--
19	9.5	119-0997	472.00	460.00	441.00	409.00	--	--
25.4	12.7	119-0998	519.00	496.00	473.00	443.00	--	--

Low Temperature - 2:1 Shrink Ratio



Black **UL** and **CSA** recognised irradiated polyolefin heat shrink tubing with a shrink ratio of 2:1 when heated to and above **80°C** making it particularly suitable for use with delicate or heat sensitive components. Flame retardant to **VW-1**, resistant to fuel, oils, hydraulic fluids and meets **UL224** and **CSA LR5659** specifications.

Dielectric strength 20kV/mm min. Operating temperature -55°C to 125°C 208006

Dia.		Order Code	Price Per Length					
Nom.	Shrunk		1+	5+	10+	25+	+	+
Black - 1.2m Lengths								
1.6	0.8	121-0327	114.00	106.00	95.00	84.00	--	--
2.4	1.2	121-0329	118.00	112.00	101.00	88.00	--	--
3.2	1.6	121-0330	128.00	122.00	110.00	96.00	--	--
4.8	2.4	121-0331	143.00	134.00	121.00	107.00	--	--
6.4	3.2	121-0332	180.00	170.00	152.00	133.00	--	--
9.5	4.7	121-0333	201.00	189.00	169.00	150.00	--	--
12.7	6.3	121-0334	232.00	219.00	196.00	174.00	--	--
19	9.5	121-0335	309.00	288.00	258.00	230.00	--	--
25.4	12.7	121-0337	488.00	456.00	410.00	364.00	--	--
Price Per Coil								
Black - 5m Coils								
1.6	0.8	121-0338	473.00	443.00	397.00	353.00	--	--
0	1.2	121-0339	440.00	420.00	387.00	370.00	--	--
3.2	1.6	121-0340	452.00	433.00	411.00	403.00	--	--
4.8	2.4	121-0341	597.00	559.00	499.00	445.00	--	--
6.4	3.2	121-0342	625.00	598.00	566.00	554.00	--	--
9.5	4.7	121-0343	749.00	714.00	652.00	626.00	--	--
12.7	6.3	121-0344	833.00	796.00	753.00	725.00	--	--
19	9.5	121-0345	1,102.00	1,052.00	996.00	955.00	--	--
25.4	12.7	121-0346	1,738.00	1,661.00	1,573.00	1,517.00	--	--

3:1 Shrink Ratio



- Black **UL224** recognised **MIL-1-23053/5**, 3:1 heat shrink when heated to 100°C
- **VW-1**, flame retardant
- Resistant to fuel, oils, hydraulic fluid

Dielectric strength 20kV/mm min. Operating temperature -55°C to +135°C 208008

Dia.		Order Code	Price Per Length					
Nom.	Shrunk		1+	5+	10+	25+	+	+
Black 1.2 Length								
1.5	0.5	119-1009	91.00	84.00	78.00	69.00	--	--
3	1	119-1010	102.00	94.00	86.00	77.00	--	--
4.5	1.5	119-1011	120.00	111.00	101.00	91.00	--	--
6	2	119-1012	152.00	140.00	128.00	114.00	--	--
9	3	119-1014	169.00	156.00	143.00	127.00	--	--
12	4	119-1015	201.00	191.00	182.00	164.00	--	--
18	6	119-1016	273.00	257.00	243.00	221.00	--	--
24	8	119-1017	412.00	392.00	378.00	331.00	--	--
39	13	119-1018	696.00	653.00	626.00	550.00	--	--
Price Per Coil								
Black 5m Coils								
1.5	0.5	119-1021	376.00	347.00	317.00	284.00	--	--
3	1	119-1022	426.00	393.00	359.00	321.00	--	--
4.5	1.5	119-1023	500.00	461.00	421.00	376.00	--	--
6	2	119-1024	629.00	580.00	530.00	473.00	--	--
9	3	119-1025	703.00	649.00	592.00	530.00	--	--
12	4	119-1026	830.00	784.00	746.00	655.00	--	--
18	6	119-1027	1,136.00	1,092.00	1,045.00	915.00	--	--
24	8	119-1028	1,720.00	1,643.00	1,581.00	1,395.00	--	--
39	13	119-1029	2,963.00	2,820.00	2,710.00	2,463.00	--	--

General Purpose Mini-Spools-3:1 Shrink Ratio



- Flexible coloured polyolefin tubing
- Good chemical and solvent resistance
- Excellent physical and electrical properties
- Wide range of colours, including Green/ Yellow Earth stripe
- Supplied on cardboard Mini-Spools
- 3:1 shrink ratio
- Flame retardant
- Minimum shrink temperature 80°C
- Operating temperature -40°C to +135°C

208297

Mini-Spools Dia.		Spool Length (m)	Order Code	Price Per Spool					
Nom.	Shrunk			1+	5+	10+	25+	+	+
Black									
3	1	10	121-0467	581.00	561.00	536.00	523.00	--	--
6	2	7	121-0468	581.00	561.00	536.00	523.00	--	--
9	3	5	121-0469	581.00	561.00	536.00	523.00	--	--
12	4	4	121-0470	581.00	561.00	536.00	523.00	--	--
18	6	3	121-0471	581.00	561.00	536.00	523.00	--	--
24	8	3	121-0472	581.00	561.00	536.00	523.00	--	--
Red									
3	1	10	121-0473	581.00	561.00	536.00	523.00	--	--
6	2	7	121-0474	581.00	561.00	536.00	523.00	--	--
9	3	5	121-0475	581.00	561.00	536.00	523.00	--	--
12	4	4	121-0477	581.00	561.00	536.00	523.00	--	--
18	6	3	121-0478	581.00	561.00	536.00	523.00	--	--
24	8	3	121-0479	581.00	561.00	536.00	523.00	--	--
Yellow									
3	1	10	121-0480	581.00	561.00	536.00	523.00	--	--
6	2	7	121-0481	581.00	561.00	536.00	523.00	--	--
9	3	5	121-0482	581.00	561.00	536.00	523.00	--	--
12	4	4	121-0483	581.00	561.00	536.00	523.00	--	--
18	6	3	121-0484	581.00	561.00	536.00	523.00	--	--
24	8	3	121-0485	581.00	561.00	536.00	523.00	--	--
Green									
3	1	10	121-0486	581.00	561.00	536.00	523.00	--	--
6	2	7	121-0487	581.00	561.00	536.00	523.00	--	--
9	3	5	121-0489	581.00	561.00	536.00	523.00	--	--
12	4	4	121-0491	581.00	561.00	536.00	523.00	--	--
18	6	3	121-0492	581.00	561.00	536.00	523.00	--	--
24	8	3	304-6394	551.00	524.00	502.00	458.00	--	--
Blue									
3	1	10	121-0493	581.00	561.00	536.00	523.00	--	--
6	2	7	121-0494	581.00	561.00	536.00	523.00	--	--
9	3	5	121-0495	581.00	561.00	536.00	523.00	--	--
12	4	4	121-0496	581.00	561.00	536.00	523.00	--	--
18	6	3	121-0497	581.00	561.00	536.00	523.00	--	--
24	8	3	121-0498	581.00	561.00	536.00	523.00	--	--
White									
3	1	10	121-0499	581.00	561.00	536.00	523.00	--	--
6	2	7	121-0500	581.00	561.00	536.00	523.00	--	--
9	3	5	121-0501	581.00	561.00	536.00	523.00	--	--