

**American Midget Fuses - continued**

**High Performance Fast Acting - 10.3 x 35mm - continued**

**BLS Series - Suitable For Multimeters - continued**

Rating	Mftrs. List No.	Order Code	1+	+	+
1A	BLS1	994-3307	163.00	--	--
3A	BLS3	994-3315	164.00	--	--

**High Performance Fast Acting - 10.3 x 38mm**



**Suitable For Multimeters**



● **UL recognised**

Voltage rating 1000V ac  
Breaking capacity 17000A @ 250V ac/dc

204529

Rating	Mftrs. List No.	Order Code	1+	5+	25+
11A	OFLU011.T..TA000	305-7460	629.00	524.00	412.00

Rating	Mftrs. List No.	Order Code	1+	5+	25+
11A	OFLU011.T.TA000	994-3340	629.00	524.00	412.00

**High Performance Fast Acting - 10.3 x 38mm**



**KLK Series - Suitable For Multimeters**



- For high ac fault current circuitry
- **UL recognised (to 3A)**
- **CSA approved**


Voltage rating 600V ac  
Breaking capacity 100000A @ 600V ac

Rating	Mftrs. List No.	Order Code	1+	10+	25+
1A	OKLK001.T.	302-9335	310.00	272.00	188.00
2A	OKLK002.T.	302-9347	369.00	315.00	228.00
3A	OKLK003.T.	302-9359	336.00	293.00	168.00
4A	OKLK004.T.	302-9360	336.00	293.00	168.00
5A	OKLK005.T.	302-9372	336.00	293.00	168.00
10A	OKLK010.T.	302-9384	369.00	315.00	228.00
15A	OKLK015.T.	302-9396	310.00	272.00	168.00
20A	OKLK020.T.	302-9402	310.00	272.00	168.00
30A	OKLK030.VX832.	302-9414	310.00	272.00	168.00

204527

Rating	Mftrs. List No.	Order Code	1+	10+	25+
1A	OKLK001.T	994-3218	310.00	272.00	188.00
2A	OKLK002.T	994-3226	369.00	315.00	228.00
3A	OKLK003.T	994-3234	336.00	293.00	168.00
4A	OKLK004.T	994-3242	336.00	293.00	168.00
5A	OKLK005.T	994-3250	336.00	293.00	168.00
10A	OKLK010.T	994-3269	369.00	315.00	228.00
15A	OKLK015.T	994-3277	310.00	272.00	158.00
20A	OKLK020.T	994-3285	310.00	272.00	158.00
30A	OKLK030.VX832	994-3293	310.00	272.00	158.00

**High Performance Fast Acting - 10.38 x 38**



**KTK Series Suitable for Multimeters**




- For high ac fault current circuitry
- **UL Recognised**
- **CSA certified**

Voltage rating 600V  
Breaking capacity 100000A @ 600V

227525

Rating	Mftrs. List No.	Order Code	1+	10+	25+
0.1A	KTK-1/10	348-2789	296.00	286.00	274.00
0.25A	KTK-1/4	348-2807	287.00	273.00	256.00
0.5A	KTK-1/2	348-2819	287.00	273.00	256.00
1A	KTK-1	348-2820	239.00	224.00	212.00
1.5A	KTK-1-1/2	348-2832	239.00	224.00	212.00
2A	KTK-2	348-2844	239.00	224.00	212.00
3A	KTK-3	348-2856	239.00	224.00	212.00
4A	KTK-4	348-2868	239.00	224.00	212.00
5A	KTK-5	348-2870	239.00	224.00	212.00
6A	KTK-6	348-2881	239.00	224.00	212.00
8A	KTK-8	348-2900	303.00	284.00	266.00
9A	KTK-9	348-2911	239.00	224.00	212.00

**High Performance Quick Blow (F) - 10.3 x 38**



**KTK-R Series**



High performance, fast acting, single-element ceramic fuses for protection of branch circuits, motor control circuits, lighting ballasts and control transformers. A grooved ferrule permits mounting in rejection-type as well as standard fuseholders. **UL Recognised and CSA approved.**

Voltage rating 600V ac  
Breaking capacity 200000A @ 600V ac

Mftrs. List No. KTK-R + Rating

204412

Rating	Order Code	1+	10+	50+	100+
1A	218-923	408.00	354.00	323.00	301.00
2A	218-935	468.00	391.00	329.00	301.00
4A	218-947	443.00	--	--	--
5A	218-959	468.00	391.00	329.00	301.00
10A	218-960	468.00	391.00	329.00	301.00
15A	218-972	468.00	391.00	329.00	301.00
20A	218-984	488.00	407.00	342.00	313.00
30A	218-996	488.00	407.00	342.00	313.00

**10 x 38mm (1 1/2") HRC Cartridge Fuses and Accessories**

**Fuseholders, DIN Rail Mounting**

**GOULD**



Single pole  
H=78, W=17.5  
D (inc. lever)=73.5  
D (excl. lever)=58  
Terminal capacity=16mm<sup>2</sup>  
Rating 32A @ 400V

Triple pole  
H=78, W=52.5  
D (inc. lever)=75.5  
D (excl. lever)=52  
Terminal capacity=16mm<sup>2</sup>  
Rating 32A @ 400V

204427

	Order Code	1+	10+	25+	50+
Single Pole	248-757	270.00	250.00	236.00	228.00
Triple Pole	542-787	1,016.00	941.00	889.00	858.00

**14 x 51mm HRC Cartridge Fuses and Accessories**

**gR, gL and aM Lines**

**GOULD**



**gR Ultra Rapid Semiconductor Fuses**

- European style industrial ceramic ultra rapid fuses for protection of thyristors, diodes, small speed drives, etc.
- **UL recognised**
- Voltage rating 700Vac (**UL**), 660Vac (**IEC**)
- Power dissipation: 6 to 10W

Mftrs. List No: 50-124-06+ Rating

204376

Rating (A)	Pre-arcing I <sup>2</sup> t	Total I <sup>2</sup> t @660V	Order Code	1+	10+	100+	250+
20	21	190	187-161	380.00	358.00	336.00	328.00
25	32	340	187-173	501.00	--	--	--
32	63	620	187-185	391.00	367.00	346.00	338.00
40	140	1050	187-197	391.00	367.00	346.00	338.00

**gL (General Line)**

- European style industrial ceramic fuses for cable protection and applications where there are no surges to be absorbed
- Manufactured in accordance with **IEC 269-2, NFC60.200, 63.210, 63.211 and UNE21.108**
- Approved by **Lloyds Register of Shipping and Bureau Veritas**

Voltage rating 690Vac (20A, 25A)  
500Vac (32A, 40A)  
400Vac (50A)

Breaking capacity 80kA (20A, 25A)  
120kA (32A upwards)

Rating (A)	Order Code	5+	25+	100+	250+
20	187-306	69.00	66.00	61.00	61.00
25	187-203	71.00	68.00	63.00	60.00
32	187-215	72.00	69.00	64.00	60.00
40	187-227	72.00	69.00	64.00	60.00
50	187-239	78.00	73.00	68.00	64.00