

TRACOPOWER TOM series are AC/DC switching power supplied for direct PCB mounting. Ideal for many applications in small industrial and consumer electronic equipments with low power requirements. Compliance with international safety and EMC standards qualify these modules for worldwide use.

- AC/DC Open Frame Module
- PCB mountable with solderpins
- Ultra compact size, 65x32x23mm (TOM12)/85x41x30 (TOM25)
- Universal input 85-264 VAC
- Input regulation <20mV
- Load regulation 12W (0-100%) <50mV
- Load regulation 25W (0-100%) <100mV

- Ripple and Noise (20Mhz Bandwidth) 12W <150mVp-p
- Ripple and Noise (20Mhz Bandwidth) 25W <200mVp-p
- Overload protection
- Conducted EMI meets EN55022, Level B
- Safety approvals to EN/IEC 60950, UL60950
- 3 year product warranty

Mfrs. List No.	Voltage Output	Output Current max. at Input 230 VAC	Output Current max. at Input 115 VAC	Order Code
TOM 12105.	5V dc	2.00A	2.00A	473-1384
TOM 12112.	12V dc	1.00A	0.84A	473-1396
TOM 12124.	24V dc	0.5A	0.42A	473-1402
TOM 25105.	5V dc	5A	5A	820-5345
TOM 25112.	12V dc	2.1A	2.1A	820-5353
TOM 25115.	15V dc	1.7A	1.7A	820-5361
TOM 25124.	24V dc	1.1A	1.1A	820-5370

385683

Mfrs. List No.	Order Code	Price Each			
		1+	5+	10+	+
TOM 12105.	473-1384	2,510.00	2,260.00	2,054.00	--
TOM 12112.	473-1396	2,510.00	2,260.00	2,054.00	--
TOM 12124.	473-1402	2,510.00	2,260.00	2,054.00	--
TOM 25105.	820-5345	3,439.00	3,213.00	3,112.00	--
TOM 25112.	820-5353	3,439.00	3,213.00	3,112.00	--
TOM 25115.	820-5361	3,439.00	3,213.00	3,112.00	--
TOM 25124.	820-5370	3,439.00	3,213.00	3,112.00	--

Mains Adaptors - Linear

AC/DC Mains Adaptor - Multi - Output



- Double insulated with thermal fuse protection
- Low-cost and lightweight
- Multiple dc output level (tamper proof - selectable by screwdriver)
- High impact moulded housing
- Supplied with an Integral 1.8M output lead and 5 interchangeable output connectors

UK Version	Output Voltage (V dc)	Max. Load	Dimensions H W D (excl pins)	Mfrs. List No.	Order Code
Unregulated	1.5/3.0/4.5/6.0/9.0	300mA	76 48.5 49	EPI	117-6600
Regulated	3.0/4.5/6.0/7.5/9.0/12.0	500mA	96 58 58.5	EP2	117-6601
Regulated	1.5/3.0/4.5/6.0/9.0	900mA	96 63 58.5	EP3	117-6603

Euro Version	Output Voltage (V dc)	Max. Load	Dimensions H W D (excl pins)	Mfrs. List No.	Order Code
Unregulated	1.5/3.0/4.5/6.0/9.0	300mA	76 48.5 49	EDV1806176	117-7092
Regulated	1.5/3.0/4.5/6.0/7.5/9.0	500mA	96 58 58.5	EDV1880998	117-7093

205850

UK Version	Order Code	Price Each			
		1+	5+	10+	+
Unregulated	117-6600	636.00	608.00	579.00	--
Regulated	117-6601	825.00	796.00	768.00	--
Regulated	117-6603	1,202.00	1,174.00	1,145.00	--


Euro Version	Order Code	Price Each			
		1+	5+	10+	+
Unregulated	117-7092	630.00	608.00	579.00	--
Regulated	117-7093	817.00	796.00	768.00	--

1,000's of products added every month, check out the very latest products, news and information at: www.farnell-newarkinone.com

The very latest NEW products

Mains Adaptors - Switch Mode

Regulated 12Vdc Switch Mode Plug-in PSUs



A range of switch mode, regulated 12Vdc UK plug-in power supplies; all units have 1.8m output leads fitted with the popular 2.1x5.5x12mm centre positive connector. The connector used is the right angled type, which helps to reduce risk of accidentally unplugging the unit.

- Approved to CE/TUV for safety & noise
- Fitted with the popular right angled 2.1x5.5x12mm C+ connector
- Operating temperature 0°C - 40°C
- Operates from 230Vac ±10%
- Short circuit protected
- 5% output tolerance
- Plugs directly into a UK socket
- Very small and lightweight

419299.406511

Output Voltage	Output Current	Order Code	Price Each	
			1+	10+
12Vdc	400mA	109-6365	589.00	559.00
12Vdc	1.25A	109-6366	735.00	698.00
12Vdc	1.5A	109-6367	802.00	768.00
12Vdc	2.1A	109-6368	901.00	858.00

5W Switch Mode Plug-in PSUs



A range of ultra small switch mode, regulated 5W UK plug-in power supplies; all units have 1.8m output leads fitted with the popular 2.1x5.5x12mm centre positive connector. The connector used is the right angled type, which helps to reduce risk of accidentally unplugging the unit.

NEW

- Approved to CE for safety & noise
- Fitted with the popular right angled 2.1x5.5x12mm C+ connector
- Operating temperature 0-40°C
- Operates from 90-264Vac
- Short circuit protected
- 5% output tolerance
- Plugs directly into UK mains socket
- Small and lightweight

Input Voltage	Frequency	Line Regulation	Load Regulation	Efficiency	Weight
90 to 264Vac	47 to 63Hz	5%	5%	60% minimum	85g

419285/437368

Output Voltage	Output Current	Mfrs. List No.	Order Code	Price Each			
				1+	10+	25+	+
5V	1A	DSA-0051-05UK.	110-1984	659.00	614.00	577.00	--
9V	0.55A	DSA-0051-09UK.	110-1986	659.00	614.00	577.00	--
12V	0.4A	DSA-0051-12UK.	110-1987	659.00	614.00	577.00	--

AC/DC Mains Adaptors Switch Mode Power Supplies



Power Supplies & DC to DC Convertors

20

Compliant Non-compliant Limited stock - RoHS replacement available

RoHS