971

## FARNELL Inone

## **Sound Level Meters**

## **Digital Sound Lever Meter**



An easy to use, hand-held, digital sound level meter.

- A weighting
- 3 ranges, 35-130dB measurement
- 3½ digit LCD
- Fast response
- Meets IEC 651 type 2 standards
- Over and under range indicator
- Data hold
- Includes owner manual
- Requires 9V battery (not included) CE marked

35-80dB/50-100dB/80-130dB Resolution 0.1dB Accuracy ±1.5dB at 1kHz(94dB level)

H=25, W=67

228191

Mftrs.			Price Each	
List No.	Order Code	1+	+	+
72 - 6635	356-2657	6,615.00		

## **Digital Sound Level Meter** 72-860A





The 72-860A is a hand held, general purpose sound meter for type 2 measurement.

- A and C weighting
- 35½ digit LCD
- 35-130dB measurement
- 2 ranges
- Meets IEC 651 type 2 standards
- ½" condenser microphone
- Fast and slow dynamic response
- Over and under range indicator Maximum level hold
- Internal oscillator for calibration
- AC and DC signal output
- RS232 interface
- Includes owners manual, 9V battery, carrying case, wind screen and adjustment screwdriver

Range Resolution Frequency Range Accuracy AC output DC output

35-90dB(low),75-130dB(high) 0.1dB 30Hz-12kHz ±2.0dB at 1kHz(94dB level) 0.65 V RMS corresponding to each range step 10mV/dBm nominal 66.68 (W) X 241.3 (L) X 25.4 (H)

336783.343913

Mftrs.		Price Each				
List No.	Order Code	1+	+	+		
72-860A	490-8430	9,846.00				



In stock and ready to despatch, 300,000 products in our Asia, US and Europe warehouses.

300,000 products at your fingertips



Test Equipment - Electrical / Environmental

RoHS

300,000 products, stocked and ready to despatch