

Building Maintenance — continued

General Purpose & Weatherproof Wood Adhesive



- One part water-resistant synthetic resin emulsion wood adhesive
- Stronger than the wood itself
- For internal and external applications
- Non-flammable and clear drying

adh46

| | Order Code | 1+ | 12+ | 24+ | 48+ | 96+ | 192+ |
|-------|------------|----|-----|-----|-----|-----|------|
| 125ml | 704-4902 | | | | | | |
| 500ml | 704-4914 | | | | | | |
| 1L | 704-4926 | | | | | | |

Liquid Nails



- Super strength multi-purpose, gap filling adhesive
- Fast grab, instant bonding
- Interior and exterior use

adh23

| | Order Code | 1+ | 12+ | 24+ | 48+ | 96+ | 288+ |
|-----------------|------------|----|-----|-----|-----|-----|------|
| 310ml Cartridge | 703-0174 | | | | | | |

Cleaner and Solvent Cement



- PVC-U pipework joining cement
- Offers a simple and quick means of constructing high-integrity leak-free joints
- Joints are often stronger than pipe or fitting
- Solvent cement manufactured to BS 4346 Part 3
- Durapipe 'MEK' cleaner for pre-assembly

2:1 ratio cement to cleaner

ipp226

| Mfrs. List No. | Order Code | 1+ | 12+ | 24+ | 48+ |
|--------------------------|------------|----|-----|-----|-----|
| Solvent 0.5 L 03 463 305 | 719-6532 | | | | |
| Cement 0.5 L 03 462 395 | 719-6544 | | | | |

General Purpose Adhesives

Clear Glue



20ml Tube

- A general purpose contact adhesive
- Suitable for bonding a wide variety of material, e.g. plastic, wood, PVC, metal, cardboard, felt, glass, fabric, cork and leather.

Note: Not suitable for polythene, polypropylene or polystyrene.

Warning: Flammable contents, do not use near any source of ignition, use in a well ventilated area.

- Please check with Sales Office for availability

CHM59X

| Order Code | 1+ | 5+ | 20+ | 50+ | 100+ |
|------------|----|----|-----|-----|------|
| | | | | | |

Electrical Insulating Tapes

Coloured



- Electrical grade 19mm and 38mm wide PVC insulating tape conforming to BS3924 and IEC454
- Available in Black and Red



| | Colour | Roll Size | Order Code | 1+ | 10+ | 50+ | 100+ |
|-----------------------|--------------|----------------------|------------|----|-----|-----|------|
| Nominal thickness | Black | 19mm x 20m | 152-346 | | | | |
| | Red | | 152-347 | | | | |
| Operating temperature | 0.15 | | | | | | |
| | 0°C to +80°C | Dielectric breakdown | | | | | |
| | | Elongation | | | | | |
| | | 40kV/mm | | | | | |
| | | 170% | | | | | |

CHM153X

| Roll Size | Order Code | 1+ | 10+ | 50+ | 100+ |
|-----------|-------------|----|-----|-----|------|
| 19mm 20m | All Colours | | | | |
| 19mm 33m | All Colours | | | | |

Coloured, Boxed




PVC insulating tape packed in a box containing 10 Black, 2 Red, 2 White, 2 Yellow, 2 Blue, 2 Brown, 2 Green and 2 Green/Yellow – Total 24 rolls of 19mm 5m tape. The tape conforms to BS3924 and IEC 454.

CAB156

| 24 Per Box | Order Code | 1+ | 10+ | 50+ | 100+ |
|------------|------------|----|-----|-----|------|
| | 305-1754 | | | | |

2705 – 'All Weather' (Black)



An electrical grade, flame retardant PVC insulating tape suitable for use over a wide range of temperatures and weather conditions. The tape conforms to BS3924 and IEC454.

| | |
|-----------------------|----------------|
| Nominal thickness | 0.175 |
| Operating temperature | -18°C to +80°C |
| Dielectric breakdown | 9kV |
| Elongation | 250% |
| Dimensions | 19mm 20m roll |
| Colour | Black |

CAB213X

| Order Code | 1+ | 10+ | 48+ | 96+ |
|------------|----|-----|-----|-----|
| 217-086 | | | | |