

## UL Hook-Up Equipment Wire — Continued

### UL1061 (300V, 80°C) CSA SR-PVC 28 AWG – 1/28 AWG (0.085mm<sup>2</sup>) – Solid

Current rating	<b>3A</b>	Insulation material	Semi-rigid PVC
Nom. outside dia.	0.84mm	Nom. wall thickness	0.25mm

#### 305m Reels

Colour	<b>Order Code</b>	Colour	<b>Order Code</b>	Colour	<b>Order Code</b>	Colour	<b>Order Code</b>
Black	711-792†	Green	711-822†	Red	711-858	Yellow	711-883†
Blue	711-809†	Grey	711-834†	Violet	711-860		
Brown	711-810†	Orange	711-846†	White	711-871		

389X

#### Price Per Reel

**MIXED QUANTITY PRICING**

1+	5+	10+	25+
----	----	-----	-----

#### 305m All Colours

†Available until stocks are exhausted

### UL1061 (300V, 80°C) CSA SR-PVC 26 AWG – 1/26 AWG (0.13mm<sup>2</sup>) – Solid

Current rating	<b>4A</b>	Insulation material	Semi-rigid PVC
Nom. outside dia.	0.91mm	Nom. wall thickness	0.25mm

#### 305m Reels

Colour	<b>Order Code</b>	Colour	<b>Order Code</b>	Colour	<b>Order Code</b>	Colour	<b>Order Code</b>
Black	711-895†	Green	711-925†	Red	711-950†	Yellow	711-986†
Blue	711-901†	Grey	711-937†	Violet	711-962†		
Brown	711-913†	Orange	711-949†	White	711-974†		

390X

#### Price Per Reel

**MIXED QUANTITY PRICING**

1+	5+	10+	25+
----	----	-----	-----

#### 305m All Colours

†Available until stocks are exhausted

### UL1061 (300V, 80°C) CSA SR-PVC 24 AWG – 1/24 AWG (0.20mm<sup>2</sup>) – Solid

Current rating	<b>6A</b>	Insulation material	Semi-rigid PVC
Nom. outside dia.	1.02mm	Nom. wall thickness	0.25mm

#### 305m Reels

Colour	<b>Order Code</b>	Colour	<b>Order Code</b>	Colour	<b>Order Code</b>	Colour	<b>Order Code</b>
Blue	712-000†	Grey	712-036†	Red	712-050†	Yellow	712-085†
Brown	712-012†	Orange	712-048†	Violet	712-061†		

391X

#### Price Per Reel

**MIXED QUANTITY PRICING**

1+	5+	10+	25+
----	----	-----	-----

#### 305m All Colours

†Available until stocks are exhausted

### UL1015 Hook Up Wire



**New**

Semi-Rigid PVC insulated tinned annealed copper Hook Up Wire. The cable is available in both 100m and 500m reels.

Construction	7/0.20mm (7 x 32)	Rated Voltage	300V
Stranded Diameter	0.60mm	Rated Temperature	80°C
AWG	24	Tensile Strength	≥20.70Mpa
Insulation	SR PVC	Elongation (Room Temp.)	≥100%
Spark Test	Insulation 3.0KV		

CAB671/SI

#### Price Per Reel

Description	<b>Order Code</b>	1+	5+	10+	20+
Blue 100m	358-6182				
Blue 500m	358-6194				
Red 100m	358-6200				
Red 500m	358-6212				
Black 100m	358-6224				
Black 500m	358-6236				

### UL1015 Hook Up Wire



Semi-Rigid PVC insulated tinned annealed copper Hook Up Wire. The cable is available in both 100m and 500m reels.

**New**

Construction	16/0.254 (16 x 30)	Rated Voltage	600V
Stranded Diameter	1.17mm	Rated Temperature	105°C
AWG	18	Tensile Strength	≥10.30MPa
Insulation	PVC	Elongation (Room Temp.)	≥100%
Spark Test	Insulation 8.0KV		

CAB672/SI

#### Price Per Reel


Description	<b>Order Code</b>	1+	5+	10+	20+
Blue 100m	358-6248				
Blue 500m	358-6250				
Red 100m	358-6261				
Red 500m	358-6273				
Black 100m	358-6285				
Black 500m	358-6297				

### Equipment Wire 2491X

#### Plain Stranded



**multicomp**



PVC insulated **BASEC** approved plain stranded copper conductors to **BS6500**. Harmonised codes **H05V-K** (0.5 to 1.0mm<sup>2</sup>) and **H07V-K** (1.5 to 2.5mm<sup>2</sup>) except yellow. Intended for use within electrical and electronic appliances, light fittings, control panels etc, where the combination of ambient temperature and load temperature rise results in a conductor temperature not exceeding 70°C.

**Best Value**

Voltage rating 300/500V (0.5 to 1.0mm<sup>2</sup>), 450/750V (1.5mm<sup>2</sup> to 2.5mm<sup>2</sup>)

Conductor Area	Conductor Size	Nominal Wall Thickness	Nominal Outside Dia.	Current Rating
0.5mm <sup>2</sup>	16/0.2	0.6	2.6	<b>3A</b>
0.75mm <sup>2</sup>	24/0.2	0.6	2.8	<b>6A</b>
1.0mm <sup>2</sup>	32/0.2	0.6	3.0	<b>10A</b>
1.5mm <sup>2</sup>	30/0.25	0.7	3.5	<b>16A</b>
2.5mm <sup>2</sup>	50/0.25	0.8	4.2	<b>25A</b>

### 0.5mm<sup>2</sup> (16/0.2mm)

#### 100m Reels

Colour	<b>Order Code</b>	Colour	<b>Order Code</b>	Colour	<b>Order Code</b>	Colour	<b>Order Code</b>
Black	.267-375	Brown	.267-399	White	.267-417	Green/yellow earth	.267-430
Blue	.267-387	Red	.267-405	Yellow	.267-429		

253

#### Price Per Reel

**MIXED QUANTITY PRICING**

1+	5+	10+	25+	50+
----	----	-----	-----	-----

#### 100m All Colours

### 0.75mm<sup>2</sup> (24/0.2mm)

#### 100m Reels

Colour	<b>Order Code</b>	Colour	<b>Order Code</b>	Colour	<b>Order Code</b>	Colour	<b>Order Code</b>
Black	.267-442	Brown	.267-466	White	.267-480	Green/yellow earth	.267-508
Blue	.267-454	Red	.267-478	Yellow	.267-491		

249

#### Price Per Reel

**MIXED QUANTITY PRICING**

1+	5+	10+	25+	50+
----	----	-----	-----	-----

#### 100m All Colours

### 1.0mm<sup>2</sup> (32/0.2mm)

#### 100m Reels

Colour	<b>Order Code</b>	Colour	<b>Order Code</b>	Colour	<b>Order Code</b>	Colour	<b>Order Code</b>
Black	.267-510	Brown	.267-533	White	.267-557	Green/yellow earth	.267-570
Blue	.267-521	Red	.267-545	Yellow	.267-569		

248

#### Price Per Reel

**MIXED QUANTITY PRICING**

1+	5+	10+	25+	50+
----	----	-----	-----	-----

#### 100m All Colours