

Van Damme Pro-Audio/Video Cable — Continued

Digital Audio Installation Cable - 1 Pair

Vandamme



- Foamed polyolefin insulation
- Recommended for MIDI and time code purposes

Pair conductor: 7/0.2mm (0.22mm²) 24AWG plain copper
 Screen: Aluminium/polyester bonded tape
 Drain wire: 7/0.20mm (0.22mm²) 24AWG tinned copper
 Attenuation (100M): 2.156dB @ 1MHz, 4.347dB @ 4MHz, 7.241dB @ 10MHz,
 8.838dB @ 16MHz, 10.236dB @ 20MHz
 Temp. range: -20°C to +70°C
 Voltage rating: 250V
 Nominal outside dia.: 3.90mm


450

Reel Length	Order Code	Price Per Reel			
		1+	5+	10+	
100m	.798-721				
500m	.798-733				

Microphone Cable

Miniature 1, 2 & 4 Core
Conductive Thermoplastic Screen

ALCATEL



Polyethylene insulated 7/0.2mm (0.22mm²) tinned copper conductors together with a 7/0.2mm tinned copper drain wire in a conductive thermoplastic sheath providing a high level of screening and flexibility. Ideal for microphones, indoor or outdoor sound installations, instrumentation applications etc. Sheathed overall in Black PVC.

Operating temperature -20°C to +80°C

No. of Cores	Nom. Outside Diameter	Capacitance/Metre Core/Core	Core/Screen	Colour Code
1	2.6	—	180pF	Clear
2	3.7	90pF	160pF	Clear, Blue
4	4.4	80pF	150pF	Clear, Blue, Red, Yellow

229

100m Reels		Price Per Reel				
No. of Cores	Order Code	1+	5+	10+	15+	20+
1	.218-091					
2	.218-108					
4	.218-110					

Flexible 2 Core
Semiconductive Plastic Screen

permanodit



Clear and Yellow polyethylene insulated 30/0.12mm (0.35mm²) tinned copper conductors laid with 30/0.12mm tinned copper drain wire in a semiconductive plastic bedding giving a high level of screening with no

degradation due to cable/screen movement. Sheathed overall in Type 8 Arctic grade PVC for high flexibility.

Nominal outside diameter 6.6mm Capacitance 91pF/m, core to core, 178pF/m, core to screen

176

100m Reels		Price Per Reel				
Colour	Order Code	1+	5+	10+	15+	20+
Blue	152-134					
Red	152-135					

'STARQUAD' 4 Core



Four twisted cores of PVC insulated 14/0.12mm (0.16mm²) plain copper conductors twisted round a centre PVC filament in a tight lay length (12.5mm) to form a balanced quad cable. Screened with helically wound

48/0.15mm tinned copper wire to ensure high quality sound transmission through electrically noisy areas. Sheathed overall in Grey PVC.

Nominal outside diameter 4.7mm Nom. capacitance per pair 115pF/m
 Pair colours Red/Blue and Green/White Mftrs. List No. 48400

171

100m Reel		Price Per Reel				
Colour	Order Code	1+	5+	10+	15+	20+
Grey	152-133					

Professional Audio Cable

7/0.254mm (Twisted Pair)

Brand-Rex



- Applications audio or data transmission

Nominal outside diameter 3.56mm Capacitance 111pF/m core to core
 Mftrs. List No. B156451 220pF/m core to screen

194

100m Reels		Price Per Reel				
Colour	Order Code	1+	5+	10+	15+	20+
Black	.152-573					
Grey	235-726					
500m Reel						
Black	.277-939					

Loudspeaker Cable
Oxygen Free Copper

multicomp



High quality **Oxygen Free Copper** with micro fine strands offering excellent flexibility. Insulated with a transparent PVC sheath ribbed on one core for identification.

Best Value

369

Reel Length	Nom.	Order Code	Price Per Reel		
	Dimensions		1+	5+	10+
1.5mm² (189/0.1mm)					
25m	6.5 3.1	711-068			
100m	6.5 3.1	711-070			
2.5mm² (322/0.1mm)					
25m	7.5 3.6	711-081			
100m	7.5 3.6	711-093			
4.0mm² (511/0.1mm)					
25m	10.2 5.0	711-100			
100m	10.2 5.0	711-111†			
6.0mm² (777/0.1mm)					
25m	12.5 6.1	711-123			
100m	12.5 6.1	711-135†			
† Available until stocks are exhausted					

† Available until stocks are exhausted

Loudspeaker Cable
LC-OFc Conductors

HITACHI



- Black and Red polyethylene insulated 54/0.18mm (1.25mm²) plain conductors using high purity **LINEAR CRYSTAL-OXYGEN FREE COPPER** in twin "figure 8" configuration

- Sheathed overall in tough matt Black PVC
- Use of LC-OFc enables high quality sound transmission due to low signal loss
- Ideal for use in low voltage, high current power supply applications.

Overall dimensions 5.0 9.4 Max voltage 100V RMS
 Max. operating temp. 60°C Max current 10A
 Max. cond. resistance 14Ω/km

172

25m Reel		Price Per Reel		
Colour	Order Code	1+	5+	10+
Black	.152-143			

Loudspeaker Cable
2.5mm² O.F.H.C.

DELTRON



- White polyethylene insulated 79/0.2mm (2.5mm²) plain stranded **O.F.H.C. (Oxygen Free High Conductivity)** copper conductors in twin "figure 8" (shot-gun construction).
- **O.F.H.C.** provides low conductor resistance enabling high quality sound transmission due to low signal loss.
- One conducto sheath ribbed for identification

Overall dimensions 3.5x7.0 Parallel capacitance 45pF/m
 Max. loop resistance 14.5Ω/km Inductance 0.583uH/m

76

100m Reel			Price Per Boxed Reel		
Colour	Mftrs. List No.	Order Code	1+	5+	10+
White	437-0010	662-173			