

Heat Shrink Tubing — Continued

134BX

Yellow – 5m Coils

Dia.		Order Code	Price Per Coil					
Nom.	Shrunk		1+	5+	10+	25+	50+	100+
1.6	0.8	236-019						
2.4	1.2	236-020						
3.2	1.6	236-032						
4.8	2.4	236-044						
6.4	3.2	236-056						
9.5	4.7	236-068						
12.7	6.3	236-070						
19.0	9.5	236-081						
25.4	12.7	236-093						

Red – 1.2m Lengths

Dia.		Order Code	Price Per Length					
Nom.	Shrunk		1+	5+	10+	25+	50+	100+
1.6	0.8	.107-473						
2.4	1.2	.107-474						
3.2	1.6	.107-475						
4.8	2.4	.107-476						
6.4	3.2	.107-477						
9.5	4.7	.107-478						
12.7	6.3	.107-479						
19.0	9.5	.107-480						
25.4	12.7	.107-481						
38.1	19.0	.107-482						
50.8	25.4	.107-483						

Red – 5m Coils

Dia.		Order Code	Price Per Coil					
Nom.	Shrunk		1+	5+	10+	25+	50+	100+
1.6	0.8	590-009						
2.4	1.2	590-010						
3.2	1.6	590-022						
4.8	2.4	590-034						
6.4	3.2	590-046						
9.5	4.7	590-058						
12.7	6.3	590-060						
19.0	9.5	590-071						
25.4	12.7	590-083						
38.1	19.0	590-095						

Blue – 1.2m Lengths

Dia.		Order Code	Price Per Length					
Nom.	Shrunk		1+	5+	10+	25+	50+	100+
1.6	0.8	.107-495						
2.4	1.2	.107-496						
3.2	1.6	.107-497						
4.8	2.4	.107-498						
6.4	3.2	.107-499						
9.5	4.7	.107-500						
12.7	6.3	.107-501						
19.0	9.5	.107-502						
25.4	12.7	.107-503						
38.1	19.0	.107-504						
50.8	25.4	.107-505						

Blue – 5m Coils

Dia.		Order Code	Price Per Coil					
Nom.	Shrunk		1+	5+	10+	25+	50+	100+
1.6	0.8	590-101						
2.4	1.2	590-113						
3.2	1.6	590-125						
4.8	2.4	590-137						
6.4	3.2	590-149						
9.5	4.7	590-150						
12.7	6.3	590-162						
19.0	9.5	590-174						
25.4	12.7	590-186						
38.1	19.0	590-198						

White – 1.2m Lengths

Dia.		Order Code	Price Per Length					
Nom.	Shrunk		1+	5+	10+	25+	50+	100+
1.6	0.8	.659-903						
2.4	1.2	.659-915						
3.2	1.6	.659-927						
4.8	2.4	.659-939						
6.4	3.2	.659-940						
9.5	4.7	.659-952						
12.7	6.3	.659-964						
19.0	9.5	.659-976						
25.4	12.7	.659-988						
38.1	19.0	.659-990						
50.8	25.4	.660-000						

White – 5m Coils

Dia.		Order Code	Price Per Coil					
Nom.	Shrunk		1+	5+	10+	25+	50+	100+
1.6	0.8	590-204						
2.4	1.2	590-216						
3.2	1.6	590-228						
4.8	2.4	590-230						
6.4	3.2	590-241						
9.5	4.7	590-253						
12.7	6.3	590-289						
19.0	9.5	590-290						

134CX

Green – 1.2m Lengths

Dia.		Order Code	Price Per Length					
Nom.	Shrunk		1+	5+	10+	25+	50+	100+
1.6	0.8	660-012						
2.4	1.2	660-024						
3.2	1.6	660-036						
4.8	2.4	660-048						
6.4	3.2	660-050						
9.5	4.7	660-061						
12.7	6.3	660-073						
19.0	9.5	660-085						
25.4	12.7	660-097						
38.1	19.0	660-103						

Green – 5m Coils

Dia.		Order Code	Price Per Coil					
Nom.	Shrunk		1+	5+	10+	25+	50+	100+
1.6	0.8	590-307						
2.4	1.2	590-319						
3.2	1.6	590-320						
4.8	2.4	590-332						
6.4	3.2	590-344						
9.5	4.7	591-336						
12.7	6.3	591-348						

Brown – 1.2m Lengths

Dia.		Order Code	Price Per Length					
Nom.	Shrunk		1+	5+	10+	25+	50+	100+
1.6	0.8	660-127						
2.4	1.2	660-139						
3.2	1.6	660-140						
4.8	2.4	660-152						
6.4	3.2	660-164						
9.5	4.7	660-176						
12.7	6.3	660-188						
19.0	9.5	660-190						
38.1	19.0	660-218†						

†Available until stocks are exhausted

Green/Yellow Earth – 1.2m Lengths

Dia.		Order Code	Price Per Length					
Nom.	Shrunk		1+	5+	10+	25+	50+	100+
3.2	1.6	.108-759						
4.8	2.4	.108-760						
6.4	3.2	.108-761						
9.5	4.7	.108-762						
12.7	6.3	.108-763						
19.0	9.5	.108-764						
25.4	12.7	.108-765						

Green/Yellow Earth – 5m coils

Dia.		Order Code	Price Per Coil					
Nom.	Shrunk		1+	5+	10+	25+	50+	100+
3.2	1.6	591-490						
4.8	2.4	591-506						
6.4	3.2	591-520						
9.5	4.7	591-579						
12.7	6.3	591-609						
19.0	9.5	591-610						
25.4	12.7	591-622						

UL Marked 2:1 Shrink Ratio



- Black **UL** approved, marked polyolefin heat shrink tubing
- Resistant to fuel, oils, hydraulic fluid
- Flame retardant to **VW-1, UL224, CSA C22.2** approved, manufactured to **MIL-DTL-23053/5**

Dielectric strength 25kV/mm min.

Operating temperature -55°C to 135°C

FOR SUITABLE HEATGUNS SEE PAGE 176

349X