

## Cable Glands — Continued

### Skintop STR



- Skintop STR with reducing seal insert
- Body: Polyamide
- Sealing: Neoprene
- Colour: Silver Grey (RAL7001)
- Protection class **IP68** (5 bar)
- Temperature range: -20°C to +80°C
- VDE, UL, CSA approval

**New**

Mftrs. List No.	Thread	Cable Dia.	A/F Size	Order Code
53015110	PG9	1.5-5	15	348-5493
53015120	PG11	2-6	19	348-5500
53015130	PG13.5	2-7	22	348-5511
53015140	PG16	4-9	24	348-5523
53015150	PG21	6-12	27	348-5535
53015160	PG29	9-16	33	348-5547
53015170	PG36	11-20	42	348-5559
53015180	PG42	17-26	53	348-5560
53015190	PG48	22-31	60	348-5572
53111100	M12	1-5	15	348-5584
53111110	M16	2-7	19	348-5596
53111120	M20	5-10	25	348-5602
53111130	M25	6-13	30	348-5614
53111140	M32	7-15	36	348-5626
53111150	M40	15-23	46	348-5638
53115160	M50	22-29	55	348-5640
53115170	M63	28-39	66	348-5651

CAB682

Mftrs. List No.	Order Code	1+	10+	50+	100+
53015110	<b>348-5493</b>				
53015120	<b>348-5500</b>				
53015130	<b>348-5511</b>				
53015140	<b>348-5523</b>				
53015150	<b>348-5535</b>				
53015160	<b>348-5547</b>				
53015170	<b>348-5559</b>				
53015180	<b>348-5560</b>				
53015190	<b>348-5572</b>				
53111100	<b>348-5584</b>				
53111110	<b>348-5596</b>				
53111120	<b>348-5602</b>				
53111130	<b>348-5614</b>				
53111140	<b>348-5626</b>				
53111150	<b>348-5638</b>				
53115160	<b>348-5640</b>				
53115170	<b>348-5651</b>				

### Skintop MSR / MSR-M



- Brass glands with reducing seal insert
- Nickel plated
- Sealing ring Neoprene
- O-Ring Pebunan
- Protection class **IP68** (5 bar)
- Temperature range: -30°C to +100°C

**New**

Mftrs. List No.	Thread	Cable Dia.	A/F Size	Order Code
52015770	PG7	2-5	14	348-5717
52015780	PG9	2-6	17	348-5729
52015790	PG11	3-7	20	348-5730
52015800	PG13.5	4-9	22	348-5742
52015810	PG16	6-13	24	348-5754
52015820	PG21	8-16	30	348-5766
52015830	PG29	10.5-20	40	348-5778
52015831	PG36	19-26	50	348-5780
52015832	PG42	24-31	57	348-5791
53112100	M12 1.5	1-5	16	348-5810
53112110	M16 1.5	2-7	20	348-5821
53112120	M20 1.5	5-10	24	348-5833
53112130	M25 1.5	6-13	29	348-5845
53112140	M32 1.5	7-15	36	348-5857
53112150	M40 1.5	15-23	45	348-5869
53112160	M50 1.5	22-29	54	348-5870
53112170	M63 1.5	28-39	67	348-5882

CAB683

Mftrs. List No.	Order Code	1+	10+	50+	100+
52015770	<b>348-5717</b>				
52015780	<b>348-5729</b>				
52015790	<b>348-5730</b>				
52015800	<b>348-5742</b>				
52015810	<b>348-5754</b>				

continued

Mftrs. List No.	Order Code	1+	10+	50+	100+
52015820	<b>348-5766</b>				
52015830	<b>348-5778</b>				
52015831	<b>348-5780</b>				
52015832	<b>348-5791</b>				
53112100	<b>348-5810</b>				
53112110	<b>348-5821</b>				
53112120	<b>348-5833</b>				
53112130	<b>348-5845</b>				
53112140	<b>348-5857</b>				
53112150	<b>348-5869</b>				
53112160	<b>348-5870</b>				
53112170	<b>348-5882</b>				

### Skindicht® SM Locknuts



- Nickel plated brass locknut to suit all brass glands

Mftrs. List No.	Thread (mm)	A/F Size (mm)	Thickness (mm)	Order Code
5200 3490	PG7	15	2.8	303-5554
5200 3500	PG9	18	2.8	303-5566
5200 3510	PG11	21	3	303-5578
5200 3520	PG13.5	23	3	303-5608
5200 3530	PG16	26	3	303-5610
5200 3540	PG21	32	3.5	303-5621
5200 3550	PG29	41	4	303-5633
5210 3000	M 12 1.5	15	3	303-5736
5210 3010	M16 1.5	19	3	303-5748
5210 3020	M20 1.5	24	3.5	303-5761
5210 3030	M25 1.5	30	4	303-5797
5210 3040	M32 1.5	36	4	303-5803
5210 3050	M40 1.5	46	5	303-5815
5210 3060	M50 1.5	60	5	303-5827
5210 3070	M63 1.5	70	5	303-5839

CAB684

Thread	Order Code	1+	10+	50+	100+
PG7	<b>303-5554</b>				
PG9	<b>303-5566</b>				
PG11	<b>303-5578</b>				
PG13.5	<b>303-5608</b>				
PG16	<b>303-5610</b>				
PG21	<b>303-5621</b>				
PG29	<b>303-5633</b>				
PG36	<b>303-5645</b>				
M 12 1.5	<b>303-5736</b>				
M16 1.5	<b>303-5748</b>				
M20 1.5	<b>303-5761</b>				
M25 1.5	<b>303-5797</b>				
M32 1.5	<b>303-5803</b>				
M40 1.5	<b>303-5815</b>				
M50 1.5	<b>303-5827</b>				
M63 1.5	<b>303-5839</b>				

### Skindicht® SM-PE Locknuts



- Nickel plated brass locknut to suit all brass glands
- Suitable for the EMC gland MS-SC
- With teeth cutting through coatings and lacque layers to ensure an electrical contact to the metal

Mftrs. List No.	Thread	A/F Size (mm)	Thickness (mm)	Order Code
5210 3200	PG7	15	4.7	303-5657
5210 3210	PG9	18	4.7	303-5669
5210 3220	PG11	21	4.7	303-5670
5210 3230	PG13.5	23	4.7	303-5682
5210 3240	PG16	26	4.7	303-5694
5210 3250	PG21	32	5.2	303-5700
5210 3260	PG29	41	5.7	303-5712
5210 3270	PG36	51	6.7	303-5724
5210 3000	M12 1.5	15	3	303-5736
5210 3010	M16 1.5	19	3	303-5748
5210 0320	M20 1.5	24	3.5	303-5761

continued