

Machine Screws - Steel

Pan Head, Pozidriv®  
Bright Zinc Plated and Clear Passivated



- Manufactured in accordance with BS4183 (metric)

H3X

| 100 Per Box   | Length | Driver Size | Order Code | Price Per Box |    |     |     |      |      |
|---------------|--------|-------------|------------|---------------|----|-----|-----|------|------|
|               |        |             |            | 1+            | 5+ | 25+ | 50+ | 100+ | 250+ |
| <b>Metric</b> |        |             |            |               |    |     |     |      |      |
| M2            | 6      | No.0        | .507-131   |               |    |     |     |      |      |
|               | 12     | No.0        | .507-143   |               |    |     |     |      |      |
| M2.5          | 6      | No.1        | .149-551   |               |    |     |     |      |      |
|               | 10     | No.1        | .149-552   |               |    |     |     |      |      |
|               | 12     | No.1        | .149-553   |               |    |     |     |      |      |
|               | 20     | No.1        | .149-554   |               |    |     |     |      |      |
| M3            | 6      | No.1        | .149-555   |               |    |     |     |      |      |
|               | 10     | No.1        | .149-556   |               |    |     |     |      |      |
|               | 12     | No.1        | .149-557   |               |    |     |     |      |      |
|               | 16     | No.1        | .149-558   |               |    |     |     |      |      |
|               | 20     | No.1        | .149-559   |               |    |     |     |      |      |
|               | 25     | No.1        | .149-560   |               |    |     |     |      |      |
| M3.5          | 6      | No.2        | .149-561   |               |    |     |     |      |      |
|               | 10     | No.2        | .149-562   |               |    |     |     |      |      |
|               | 12     | No.2        | .149-563   |               |    |     |     |      |      |
|               | 16     | No.2        | .149-564   |               |    |     |     |      |      |
| M4            | 6      | No.2        | .149-566   |               |    |     |     |      |      |
|               | 10     | No.2        | .149-567   |               |    |     |     |      |      |
|               | 12     | No.2        | .149-568   |               |    |     |     |      |      |
|               | 16     | No.2        | .149-569   |               |    |     |     |      |      |
| M5            | 6      | No.2        | .149-574   |               |    |     |     |      |      |
|               | 10     | No.2        | .149-575   |               |    |     |     |      |      |
|               | 12     | No.2        | .149-576   |               |    |     |     |      |      |
|               | 16     | No.2        | .149-577   |               |    |     |     |      |      |
|               | 20     | No.2        | .149-578   |               |    |     |     |      |      |
|               | 25     | No.2        | .149-579   |               |    |     |     |      |      |
| M6            | 12     | No.3        | .149-581   |               |    |     |     |      |      |
|               | 16     | No.3        | .149-582   |               |    |     |     |      |      |
|               | 20     | No.3        | .149-583   |               |    |     |     |      |      |
|               | 25     | No.3        | .149-584   |               |    |     |     |      |      |
| 40            | No.3   | .149-585    |            |               |    |     |     |      |      |

Pan Head, Pozidriv®  
Black Zinc Passivated



- Manufactured in accordance with BS4183
- Suitable for use in areas requiring low light reflection or simply for a cosmetic effect

H104X

| 100 Per Box | Length | Order Code | Price Per Box |    |     |     |      |      |  |
|-------------|--------|------------|---------------|----|-----|-----|------|------|--|
|             |        |            | 1+            | 5+ | 25+ | 50+ | 100+ | 250+ |  |
| M3          | 6      | No.1       | .250-387      |    |     |     |      |      |  |
|             | 10     | No.1       | .250-399      |    |     |     |      |      |  |
|             | 12     | No.1       | .250-405      |    |     |     |      |      |  |
| M4          | 6      | No.2       | .250-417      |    |     |     |      |      |  |
|             | 10     | No.2       | .250-429      |    |     |     |      |      |  |
|             | 12     | No.2       | .250-430      |    |     |     |      |      |  |
| M5          | 10     | No.2       | .250-442      |    |     |     |      |      |  |
|             | 12     | No.2       | .250-454      |    |     |     |      |      |  |
|             | 16     | No.2       | .250-466      |    |     |     |      |      |  |
| M6          | 12     | No.3       | .250-478      |    |     |     |      |      |  |
|             | 16     | No.3       | .250-480      |    |     |     |      |      |  |
|             | 20     | No.3       | .278-774      |    |     |     |      |      |  |

Pan Head, Slotted  
Bright Zinc Plated and Clear Passivated



- Manufactured in accordance with BS4183

100 Per Box

| Length        | Order Code | Price Per Box |    |     |     |      |      |
|---------------|------------|---------------|----|-----|-----|------|------|
|               |            | 1+            | 5+ | 25+ | 50+ | 100+ | 250+ |
| <b>Metric</b> |            |               |    |     |     |      |      |
| M2            | 6          | .507-118      |    |     |     |      |      |
|               | 12         | .507-120      |    |     |     |      |      |
| M2.5          | 6          | .149-501      |    |     |     |      |      |
|               | 10         | .149-502      |    |     |     |      |      |
|               | 12         | .149-503      |    |     |     |      |      |
|               | 20         | .149-504      |    |     |     |      |      |
| M3            | 6          | .149-505      |    |     |     |      |      |
|               | 10         | .149-506      |    |     |     |      |      |
|               | 12         | .149-507      |    |     |     |      |      |
|               | 16         | .149-508      |    |     |     |      |      |
|               | 20         | .149-509      |    |     |     |      |      |
|               | 25         | .149-510      |    |     |     |      |      |
| M3.5          | 6          | .149-511      |    |     |     |      |      |
|               | 10         | .149-512      |    |     |     |      |      |
|               | 12         | .149-513      |    |     |     |      |      |
|               | 20         | .149-515      |    |     |     |      |      |
| M4            | 6          | .149-516      |    |     |     |      |      |
|               | 10         | .149-517      |    |     |     |      |      |
|               | 12         | .149-518      |    |     |     |      |      |
|               | 16         | .149-519      |    |     |     |      |      |
|               | 20         | .149-520      |    |     |     |      |      |
|               | 25         | .149-521      |    |     |     |      |      |
| M5            | 6          | .149-524      |    |     |     |      |      |
|               | 10         | .149-525      |    |     |     |      |      |
|               | 12         | .149-526      |    |     |     |      |      |
|               | 16         | .149-527      |    |     |     |      |      |
| M6            | 12         | .149-531      |    |     |     |      |      |
|               | 16         | .149-532      |    |     |     |      |      |
|               | 20         | .149-533      |    |     |     |      |      |
|               | 30         | .149-534      |    |     |     |      |      |
| 40            | .149-535   |               |    |     |     |      |      |

H2X

Pan Head, Slotted  
Black Zinc Passivated



- Manufactured in accordance with BS4183
- Suitable for use in areas requiring low light reflection or for cosmetic effect

H166X

| 100 Per Box | Length | Order Code | Price Per Box |    |     |     |      |      |
|-------------|--------|------------|---------------|----|-----|-----|------|------|
|             |        |            | 1+            | 5+ | 25+ | 50+ | 100+ | 250+ |
| M3          | 6      | .753-191   |               |    |     |     |      |      |
|             | 10     | .753-208   |               |    |     |     |      |      |
|             | 12     | .753-210   |               |    |     |     |      |      |
| M4          | 6      | .753-221   |               |    |     |     |      |      |
|             | 10     | .753-233   |               |    |     |     |      |      |
|             | 12     | .753-245   |               |    |     |     |      |      |
| M6          | 12     | .753-282   |               |    |     |     |      |      |
|             | 16     | .753-294   |               |    |     |     |      |      |
|             | 20     | .753-300   |               |    |     |     |      |      |

Pan Head, 'TORX'®  
Bright Zinc Plated and Clear Passivated



- Manufactured to BS4183 and BS3643
- Design enables high torque transfer from tool to screw
- Driving blade is very unlikely to slip out of the recess.

H105X

| 100 Per Box | Length | Driver Size | Order Code | Price Per Box |    |     |     |      |      |
|-------------|--------|-------------|------------|---------------|----|-----|-----|------|------|
|             |        |             |            | 1+            | 5+ | 25+ | 50+ | 100+ | 250+ |
| M2.5        | 6      | T8          | .250-089   |               |    |     |     |      |      |
| M3          | 6      | T10         | .250-107   |               |    |     |     |      |      |
|             | 12     | T10         | .250-119   |               |    |     |     |      |      |
|             | 20     | T10         | .250-120   |               |    |     |     |      |      |
| M4          | 6      | T20         | .250-156   |               |    |     |     |      |      |
|             | 12     | T20         | .250-168   |               |    |     |     |      |      |
|             | 20     | T20         | .250-170   |               |    |     |     |      |      |
| M5          | 12     | T25         | .250-181   |               |    |     |     |      |      |
|             | 20     | T25         | .250-193   |               |    |     |     |      |      |

Pan Head, Tamper-Proof 'TORX'®  
Bright Zinc Plated and Clear Passivated



- Tamper-proof design
- Manufactured to BS4183 and BS3643
- Spigot prevents use of standard TORX® driver
- High torque transfer from tool to screw