



## Clamps, Cable/Conduit Galvanised and Passivated





Ideal for clamping conduit, cable or pipes along the length of steelwork.

H351

A	Mfrs.		Price Each				
	List No.	Order Code	1+	25+	100+	250+	500+
37	ECH-37	326-9541					
45	ECH-45	326-9553					
49	ECH-49	326-9565					

## Conduit Clip, Universal Flange Mechanically Galvanised and Passivated





- Horizontal/vertical universal fitting
- Re-usable locking clip
- Suitable for 19-26mm dia. PG Type 13.5/16 Conduit
- Internal/external use, humid and mildly corrosive environment

Max. Loading 45kg

H352

T	Ø	Mfrs. List No.		Price Each				
		Order Code	1+	25+	100+	250+	500+	
3-8	19-26	EH38-GM1926	326-9577					
8-14	19-26	EH814-GM1926	326-9589					

## Pipe Support Clip





- Plastic clip and galvanised steel fixing
- Assists thermal insulation
- Ideal for mounting pipe/conduit along steel flanges
- Internal/external use, humid and mildly corrosive environment

H353

T	ØA	Mfrs. List No.		Price Each				
		Order Code	1+	25+	100+	250+	500+	
3-8	22	EH38-P22	326-9619					
3-8	28	EH38-P28	326-9620					
8-14	22	EH814-P22	326-9632					
8-14	28	EH814-P28	326-9644					

## Conduit Clip, Screw Fixing Mechanically Galvanised and Passivated





- Standard conduit clip
- Re-usable locking action
- Suitable for 19-26mm dia. PG Type 13.5/16 Conduit

Max. Loading 45kg

H354

ØA	Mfrs. List No.		Order Code	Price Each			
	1+	50+		100+	500+	1000+	
19-26	GM-1926	326-9840					

## Channel Clamp Galvanised Steel



- Mount cable/conduit to channels with min. 18mm slot
- Internal/external use, humid and mildly corrosive environments



Max. Loading 60kg

A = 18 Min.



H355

Ø	Mfrs. List No.		Order Code	Price Each			
	1+	25+		100+	250+	500+	
14-18	S-1418	326-9863					
18-22	S-1822	326-9875					

## Threaded Rod Hanger Mechanically Galvanised and Passivated



Horizontal



Vertical

- Horizontal or vertical flange versions
- Threaded impression or clearance hole
- Internal/external use, humid and mildly corrosive environments

Max. Loading 68kg

H356

T	Ø	A	Mfrs. List No.		Order Code	Price Each				
			1+	25+		100+	250+	500+		
<b>Horizontal</b>										
3-8	M6	46	AH38-AM6T	327-1535						
8-14	M6	54	AH814-AM6T	327-1547						
14-20	M6	66	AH1420-AM6T	327-1559						
3-8	M10	46	AH38-AM10T	327-1560						
8-14	M10	54	AH814-AM10T	327-1572						
14-20	M10	66	AH1420-AM10T	327-1584						
<b>Vertical</b>										
1.5-5	M6	70	AV155-AM6T	327-1699						
5-7	M6	70	AV57-AM6T	327-1705						
1.5-5	M8	70	AV155-AM8T	327-1717						
5-7	M8	70	AV57-AM8T	327-1729						
1.5-5	M10	70	AV155-AM10T	327-1730						
5-7	M10	70	AV57-AM10T	327-1742						
1.5-5	12.7	70	AV155-AM127	327-1754						

continued