

Baths

0.6, 4.9 and 12 Litres



- Sturdy 304 stainless construction
- Ultrasonic cleaners in three capacities
- 12 month warranty on parts and labour, 2 year on transducer bonding

All are supplied with an ASTA approved plug fitted.

| | | |
|--------------------|--------------------|--------------------|
| Order Code | 299-364 | 299-376 |
| Mfrs. List No. | T80 | 575 |
| Tank capacity | 0.6 litres | 4.9 litres |
| Tank dimensions | 151 83 65 | 300 150 150 |
| Operating voltage | 220/240V - 50/60Hz | 220/240V - 50/60Hz |
| Power consumption | 60W | 460W |
| H.F. Peak power | 80W | 300W |
| Timer | 0 - 15 mins | 0 - 15 mins |
| Heater temperature | NONE | off/on 60°C fixed |
| Drain tap | NONE | NONE |

pcb85

| Capacity | Order Code | 1+ | 3+ | 6+ |
|------------|----------------|----|----|----|
| 0.6 litres | 299-364 | | | |
| 4.9 litres | 299-376 | | | |

Tank Accessories



- Plastic lids and stainless steel baskets for ultrasonic tanks

| | | |
|-----------|------------|------------|
| Tank size | 0.6 litres | 4.9 litres |
| Lid | 108-099 | 108-100 |
| Basket | — | 108-102 |

pcb86

| | Order Code | 1+ | 3+ | 6+ |
|-------------------|----------------|----|----|----|
| Lid 0.6 litres | 108-099 | | | |
| Lid 4.9 litres | 108-100 | | | |
| Basket 4.9 litres | 108-102 | | | |

Meters

pH Logger Hanna 'pH Turtle'



- Turns your PC into a pH meter
- Continuous logging on your monitor
- Data in graphic or table format
- Min and max alarm settings
- No need for power supply or serial box
- System includes pH turtle, pH electrode, Windows® software and RS232 cable

| | |
|--------------|------------------------|
| Range | 0.0 to 14.0 pH |
| Resolution | 0.1 pH |
| Accuracy | ±0.2 pH |
| pH Electrode | HI 1333B with 1m cable |
| Environment | 0 to 50°C |
| Dimensions | 80mm diameter |
| Weight | 250g |

teq91

| Mfrs. List No. | Order Code | 1+ | 5+ | 10+ | 20+ |
|----------------|-----------------|----|----|-----|-----|
| HI-9815 | 725-9128 | | | | |

Pre-Mixed Calibration Solutions pH and Conductivity



- Available for both Conductivity and pH calibration
- Pre-mixed for ease of use
- Supplied with calibration chart
- Available for a range of values

lin150

| pH Buffer Solutions 460ml | Order Code | 1+ | 5+ | Price Each | | |
|--|-----------------|----|----|------------|-----|-----------|
| | | | | 10+ | 50+ | 100+ 250+ |
| pH 4.01 | 710-5423 | | | | | |
| pH 7.01 | 710-5435 | | | | | |
| pH 10.01 | 710-5447 | | | | | |
| Conductivity Calibration Solutions 460ml | | | | | | |
| 12,880µS/cm | 710-7365 | | | | | |
| 1413µS/cm | 710-7377 | | | | | |
| 84µS/cm | 710-7389 | | | | | |

pH Buffer Solutions



- Single use pH buffer solutions
- Each 25ml sachet contains enough solution for one calibration
- Simple to use, open sachet, insert tester and calibrate
- No extra containers required
- No solution is wasted
- Sachets are supplied in packs of 25

teq92

| 25 Per Pack | Mfrs. List No. | Order Code | 1+ | 5+ | 10+ | 20+ |
|-------------|----------------|-----------------|----|----|-----|-----|
| 4.01 pH | HI-70004P | 725-9130 | | | | |
| 7.01 pH | HI-70007P | 725-9141 | | | | |
| 10.1 pH | HI-70010P | 725-9153 | | | | |

Bench pH Meter



- Large clear LCD displays pH/mV with °C
- Automatic calibration with choice of 5 buffers
- User-friendly operation with LCD icons
- Automatic or manual temperature compensation
- Supplied with glass bodied combination pH electrode, temperature probe

Advanced microprocessor bench pH meter for accurate measurement of pH, ion selective readings redox and temperature across a wide range of applications. Exceptionally user-friendly with graphic icons on the large LCD to guide the user through calibration, correct buffer choice, stable readings and problem solving. Calibration is automatic with a choice of 5 buffers. Readings can be temperature compensated either automatically or manually from 0°C to 100°C. Supplied complete with glass combination pH electrode, temperature probe and starter pack including buffer solutions 4 and 7, electrolyte and cantilever electrode holder.

| | |
|--------------|---------------------------|
| Range | pH 0.00 to 14.00 |
| mV | ±399.9 (ISE), ±1999 (ORP) |
| °C | 0.0 to 100.0 |

| | |
|-------------------|---------------------|
| Resolution | pH 0.01 |
| mV | 0.01 (ISE), 1 (ORP) |
| °C | 0.1 |

| | |
|-----------------|----------------------|
| Accuracy | pH ±0.01 |
| mV | ±0.2 (ISE), ±1 (ORP) |
| °C | ±0.5 |

| | |
|--------------------------|--|
| Temperature Compensation | Auto or manual: 0.0°C to 100.0°C |
| Calibration | Auto with a choice of 5 buffers (4.01, 6.86, 7.01, 9.18, 10.01) |
| Power Supply | 12V dc adaptor |
| Dimensions | 230 170 70mm |
| Weight | Kit 3.2 kg |



lin52

| Mfrs. List No. | Order Code | 1+ | 5+ | 10+ | 50+ | 100+ |
|----------------|-----------------|----|----|-----|-----|------|
| HI-9321 | 710-5563 | | | | | |