

Beacons

Mini-Strobe Xenon



Recent Addition

Drive module: 62 x 33 x 22mm
Lamp unit: 79 x 31 x 21mm

- Compact and reliable xenon flashing devices for integration into a wide range of applications
- Complete beacon comprises a drive module and xenon tube mounted in a neat weatherproof housing
- Xenon tube weatherproofed to **IP67**
- Applications include security, alarm panels, door entry controls etc.

Voltage	Power Output	Current Consumption (mA)	Flash Rate Nominal	Weight (gms)	Order Code
12V	1W	115	60/min	65	353-9507
24V	1W	55	60/min	65	353-9519


SSW359

Order Code	Price Each				
	1+	10+	20+	50+	100+
Drive modules					
12V	353-9507				
24V	353-9519				
Xenon lamps					
Amber	353-9520				
Red	353-9532				
Blue	353-9544				
Green	353-9556				

Low Profile, 1 Watt



Beacon H = 45, 60
(mounting base fitted) Dia = 77



Drilling pattern for bell box or panel mounting

Mounting base

- Low profile, low current, high efficiency xenon beacons fitted with a coloured lens sealed to **IP67**.
- Surface mounting a base is available separately.
- Accessories are included to enable the beacons to be bayonet fitted onto a mounting base.

Flash rate	1 per second	Voltage range	12V dc	10 to 15V
Connection	Flying lead 500mm Red +ve, Black -ve		24V dc	20 to 30V
		Current	12V dc	115mA
			24V dc	55mA

SSW47X

Colour	Order Code	Price Each				
		1+	10+	20+	50+	100+
12V dc						
Amber	223-700					
Clear	223-712					
Red	223-724					
Blue	223-736					
24V dc						
Amber	223-748					
Clear	223-750					
Red	223-761					
Blue	223-773					
Mounting base	223-785					

Multi-voltage Xenon Beacons



- Low current consumption range of xenon beacons
- Weatherproof to **IP67** when installed
- Low profile and standard height versions available in two colours and two power outputs
- Supplied with 500mm flying leads
- 360° visibility
- Separate mounting bracket available which allows wiring from the side as well as from the base

Recent Addition

Low profile: H = 45mm Dia. = 77mm
Standard: H = 95mm Dia = 77mm

Colour	Power Output	Current Consumption (mA)			Flash Rate	Order Code
		@12V	@24V	@50V		
Amber	1W	112	63	50	29	60/Min 353-9416
Red	1W	112	63	50	29	60/Min 353-9428
Amber	2W	130	95	83	37	75/Min 353-9430
Red	2W	130	95	83	37	75/Min 353-9441
Amber	2W	130	95	83	37	75/Min 353-9453
Red	2W	130	95	83	37	75/Min 353-9465
Amber	5W	255	190	112	70	75/Min 353-9477
Red	5W	255	190	112	70	75/Min 353-9489

Voltage range 10-100V dc
20-72V ac

SSW358

Colour	Power	Order Code	Price Each				
			1+	10+	20+	50+	100+
Low Profile							
Amber	1W	353-9416					
Red	1W	353-9428					
Amber	2W	353-9430					
Red	2W	353-9441					
Standard							
Amber	2W	353-9453					
Red	2W	353-9465					
Amber	5W	353-9477					
Red	5W	353-9489					
Mounting Bracket		353-9490					

Standard Beacon

MICOTECH



- Choice of coloured polycarbonate lens
- Emits an intense pulse of light at one second intervals
- Sealed to **IP65** and suitable for warning and alarm application
- All 3w beacons are supplied with mounting base
- Easy connection by removable terminal block
- 12/24V versions configured with wiring options on the terminal block

SSW306

Colour	Order Code	Price Each			
		1+	10+	25+	50+
Low Profile 12V/24V DC 2W					
Amber	188-438				
Clear	188-440				
Red	188-451				
Blue	188-463				
Green	188-475				
12V/24V DC 3W					
Amber	188-281				
Clear	188-293				
Red	188-300				
Blue	188-311				
Green	188-323				
110V AC 3W					
Amber	188-335				
Clear	188-347				
Red	188-359				
Blue	188-360				
Green	188-372				
230V AC 3W					
Amber	188-384				
Clear	188-396				
Red	188-402				
Blue	188-414				
Green	188-426				

Continued