

Hand-Held Autoranging M20



169mm x 28mm (not including Probe portion)
Weight approx 60gm

- Compact 3½ digit LCD
- Pen type Probe
- Lightweight, compact and easy to use
- Measures ac/dc voltage and resistance
- Buzzer for audible continuity testing
- Display hold
- EMC meets EN50081-1 and EN50082-1

Ranges	
dc Voltage	420mv to 500V
ac Voltage	4.2V to 500V
Resistance	420Ω to 4.2 mΩ
Continuity beeper	420Ω range, Max threshold level 30Ω to 50Ω



T325

Mfrs. List No.	Order Code	1+	5+	10+
M20	C2 768-674			
Standard Calibration Charge		S C2	Each	☎

M5000 Series



- Tough, shock-resistance watertight seals
- 3½ digit LCD
- 0.5% basic accuracy
- Large character LCD
- Automatic switch off
- M5091 - 1,999 counts extra large characters for measurements in poor lighting conditions
- M5097 - 3,200 counts 65 segment analogue display, dual display for measuring varying levels autoranging or manual ranging and data hold
- Protective holster and test leads



Ranges	M5091	M5097
dc voltage	200mV to 900V	300mV to 1000V
ac voltage	200mV to 600V	3V to 750V
Current (dc and ac)	200µA to 20A	300µA to 20A
Resistance	200Ω to 20mΩ	300Ω to 30mΩ
Continuity Buzzer	1.5mA max test current	
Diode test	3.3V max O/C voltage	
Battery supplied with meter	PP3 (300hrs)	PP3 (700hrs)

T337

Mfrs List No	Order Code	1+	5+	10+
M5091	C4 768-686			
M5097	C4 768-698			
Standard Calibration Charge		S C4	Each	☎

Pocket DMM with Bargraph 72-4040



The 72-4040 is a small pocket multimeter supplied with a folding vinyl case and integral test leads.

- 3½ digit, 3200 count display with analogue bargraph
- Autoranging
- Data hold, range hold
- Diode test and continuity tester
- Auto power off
- Overload protection
- Includes battery, test leads and owners manual

DC voltage	300mV-450V	Resistance	300Ω-30MΩ
AC volts	3V-450V	Dimensions	57.15 (W) x 19.05 (H) x 107.95 (L)

T586

	Order Code	1+	5+	10+
72-4040	342-1491			

Autoranging Digital Multimeter



The 72-2050 is a rugged low cost multimeter with current input warning, auto power off and fused current inputs.



- Large 3½ digit, 3200 count LCD
- 34 segment bargraph display
- 2 times per second measuring rate
- Auto/manual range selection
- Overload protection on all ranges
- Diode test and continuity beeper
- CE marked, meets IEC-1010 safety standards for 600V CAT III applications
- Includes 9V battery, holster, test leads and owners manual

DC voltage	320mV-600V	Resistance	320Ω-30MΩ
AC voltage	3.2V-600V	Dimensions	69.85 (W) x 146.05 (H) x 38.10 (D)
DC/AC current	320µA-320mA/10A		

T577

	Order Code	1+	5+	10+
72-2050	342-1508			

Manual Ranging DMM 72-2055



The 72-2055 is a fully featured digital multimeter with a large 3½ digit display.



- 1999 count LCD
- Auto polarity indicator
- Over range indicator
- Low battery indicator
- Overload protection on all ranges
- Safety test leads and input jacks
- Transistor test and battery test
- Diode test
- CE marked, meets IEC-1010 safety standards for 600V CAT III
- Includes 9V battery, holster, test leads and owners manual

DC voltage	2V-600V	Transistor test	0-1000 hFE (NPN/PNP)
AC voltage	200V, 600V	Battery test	1.5V, 9V
DC current	0-2A	Dimensions	69.85 (W) x 146.05 (H) x 38.10 (D)
Resistance	200Ω-2000KΩ		

T589

	Order Code	1+	5+	10+
72-2055	342-1510			

continued

Call for Latest Pricing

Products on this page may be subject to price changes in line with market trends. Call us for an update on (65) 788 0200.

☎ Please call our sales office