

Conecuts

Conecut Drills

G&J HALL LTD




- The 'Conecut' is suitable for use in industrial power tools for the rapid drilling of clean holes
- For use in thin materials including sheet steel up to 2mm thick
- All Conecuts drill their own pilot hole
- Conical shape of the tool enables any size of hole to be drilled between the bottom and the top of the taper.
- All with 9.5mm shank except Order Code 100-676 which is 6mm

act329

		Order Code	1+	4+	20+
3-14mm	($\frac{1}{8}$ "- $\frac{9}{16}$ ")	100-676			
6-20mm	($\frac{1}{4}$ "- $\frac{3}{8}$ ")	.100-677			
8-22.5mm	($\frac{5}{16}$ "- $\frac{15}{16}$ ")	.104-211			
16-30mm	($\frac{5}{8}$ "- $1\frac{3}{16}$ ")	.100-678			
25-40mm	(1 "- $1\frac{5}{8}$ ")	.100-679			

CONECUT™ Trepanning Action High Speed Steel

HALL



- Trepanning action Conecut®
- Various sizes of large diameters can be drilled without a pilot hole
- Multi-flute action ensures smooth round holes

Range mm	Shank Size	Drilling speeds		Mfrs. List No.	Order Code
		Ferrous	Non Ferrous		
34-51	13	50-200	200-400	TCC3451	701-2690
43-60	13	50-150	150-400	TCC4360	701-2706

ACT37

Order Code	1+	4+	10+	20+	40+
701-2690					
701-2706					

Counterbores

Counterbores



- HSS counterbores for recessing holes to accommodate cap screws
- Also suitable for spot facing
- Conforms to **BS328 Part 5, ISO and DIN373**
- Supplied in a strong metal case

RUKO

act326

Size	Order Code	1+	4+	20+
M3	282-364			
M4	282-376			
M5	282-388			
M6	282-390			
M8	282-406			
M10	282-418			
Set of above	.282-420	1+	3+	6+

Countersinks

Pilot Drill, Clearance, Countersink and Counterbore Set

DURATOOL

New



- Set of 4 drills and attachments to make pilot holes, clearance, countersink and counterbore in one action

Order Code	1+	Price Each	5+	10+
312-7047				

act368

Rose Countersink



Record

- Manufactured with 18% Tungsten High Speed Steel
- $\frac{1}{4}$ " \varnothing shank x $1\frac{1}{16}$ " overall, $\frac{1}{2}$ " nominal head \varnothing

act330

Mfrs. List No.	Order Code	1+	Price Each	4+	20+
852	.442-902				

90° HSS, 3 Flute



RUKO

- Precision 3 flute HSS Countersinks for most ferrous and non-ferrous metals
- Design gives good chip clearance and accuracy
- All cutting and clearing surfaces are ground to prevent clogging
- Set of 5 supplied in a plastic case complete with 50ml of cutting fluid
- Fluid is for use when continuous feed lubrication/coolant is not available

Countersink Diameter mm	Overall Length mm	Shaft Length mm	Shaft Diameter mm	Order Code
6.3	45	37	5	483-783
10.5	50	38	6	483-795
16.4	59	43	8	483-801
20.5	62	42	10	483-813
25.0	66	42	10	483-825

act332

Countersinks	Order Code	1+	Price Each	4+	20+
6.3mm	483-783				
10.5mm	483-795				
16.4mm	483-801				
20.5mm	483-813				
25.0mm	483-825				
Set	483-837				
Lubricant	483-771.				

Countersinks 3-Flute High Speed Steel

HALL



- HSS countersinks
- Suitable for use on metal
- 3 flutes with a 90° angle

\varnothing	Nominal Length	Shank \varnothing	Mfrs. List No.	Order Code
6.3	45	5	CS3 6	701-4582
8.3	50	6	CS3 8	701-4594
10.4	50	6	CS3 10	701-4600
12.4	56	8	CS3 12	701-4612
16.5	60	10	CS3 16	701-4624
20.5	63	10	CS3 20	701-4636
31.0	71	12	CS3 31	701-4661

ACT39

\varnothing	Order Code	1+	4+	Price Each	10+	20+	40+
6.3	701-4582						
8.3	701-4594						
10.4	701-4600						
12.4	701-4612						
16.5	701-4624						
20.5	701-4636						
31.0	701-4661						

Countersinks 5-Flute High Speed Steel

HALL



- HSS countersinks
- Suitable for use on metal or wood
- 5 flutes with a 90° angle

\varnothing	Overall Length	Shank \varnothing	Shank Length	Mfrs. List No.	Order Code
8	35	5.00	20.5	CS5 8	701-4120
12	39	6.35	20.5	CS5 12	701-4132
16	52	8.00	32.0	CS5 16	701-4144
20	58	10.00	35.0	CS5 20	701-4156