

Mfr.	Pins	Pkg	Description	Mfrs. List No.	Order Code	Price Each			
						1+	10+	100+	
Transmitters/Receivers									
487	MAX	8	SOIC	RS485/RS422, Low Power, limited slew rate Transmitter/Receiver with \pm 15kV ESD protection, Receiver/Driver enable	MAX487ECSPA+	972-4532	166.00	127.00	91.00
488	MAX	8	DIL	RS485/RS422, Low Power, limited slew-rate Transmitter/Receiver with thermal shutdown, 250kbps data rate for Duplex applications	MAX488CPA+	972-5598	162.00	124.00	100.00
488	MAX	8	SOIC	RS485/RS422, Low Power, limited slew-rate Transmitter/Receiver with thermal shutdown, 250kbps data rate for Duplex applications	MAX488CSA	353-4170	168.00	129.00	103.00
488	MAX	8	SOIC	RS485/RS422, Low Power, limited slew-rate Transmitter/Receiver with thermal shutdown, 250kbps data rate for Duplex applications (IND TEMP)	MAX488ECSA+	972-4966	168.00	129.00	103.00
488	MAX	8	SOIC	RS485/RS422, Low Power, limited slew-rate Transmitter/Receiver with thermal shutdown, 250kbps data rate for Duplex applications (IND TEMP)	MAX488ECSA	353-4182	206.00	158.00	126.00
488	MAX	8	SOIC	RS485/RS422, Low Power, limited slew-rate Transmitter/Receiver with thermal shutdown, 250kbps data rate for Duplex applications (IND TEMP)	MAX488ECSA+	972-4974	206.00	158.00	112.00
488	MAX	8	SOIC	RS485/RS422, Low Power, limited slew-rate Transmitter/Receiver with thermal shutdown, 250kbps data rate for Duplex applications	MAX488EESA.	490-4965	274.00	210.00	168.00
489	MAX	14	DIL	RS485/RS422, Low power, Limited slew rate Transmitter/Receiver with Receiver/driver enable.	MAX488EESA+	972-5601	282.00	216.00	154.00
489	MAX	14	SOIC	RS485/RS422, Low Power, limited slew rate Transmitter/Receiver with Receiver/Driver enable.	MAX489CPD+	972-5148	137.00	105.00	75.00
489	LT	16	DIL	Quad RS485 Differential Bus/Line Receiver	MAX489CSD+	972-4559	137.00	105.00	84.00
489	LT	16	DIL	Quad RS485 Differential Bus/Line Receiver	LTC489CN	476-7779	366.00	264.00	238.00
490	LT	8	DIL	CMOS Differential Driver and Receiver	LTC490CN#PBF	956-1358	366.00	234.00	191.00
490	LT	8	DIL	CMOS Differential Driver and Receiver	LTC490CN8	386-2653	246.00	168.00	144.00
490	LT	8	SOIC	Multipoint Differential Driver and Receiver Pair	LTC490CN8#PBF	956-1366	280.00	179.00	144.00
490	LT	8	SOIC	Multipoint Differential Driver and Receiver Pair	LTC490CS8#PBF	956-1374	303.00	194.00	158.00
490	LT	8	SOIC	Multipoint Differential Driver and Receiver Pair	LTC490CS8	476-7780	303.00	218.00	197.00
490	LT	8	DIL	CMOS Differential Driver and Receiver (IND TEMP)	LTC490IN8	386-2665	303.00	218.00	197.00
490	LT	8	DIL	CMOS Differential Driver and Receiver (IND TEMP)	LTC490IN8#PBF	956-1382	344.00	220.00	177.00
490	MAX	8	SOIC	RS485/RS422, Low Power Transmitter/Receiver with thermal shutdown, 2.5Mbps data rate for Duplex applications	MAX490CSA+	972-4982	168.00	129.00	103.00
490	MAX	8	SOIC	RS485/RS422, Low Power Transmitter/Receiver with thermal shutdown, 2.5Mbps data rate for Duplex applications	MAX490EESA+	972-5610	282.00	216.00	174.00
490	MAX	8	SOIC	RS485/RS422, Low Power Transmitter/Receiver with thermal shutdown, 2.5Mbps data rate for Duplex applications	MAX490ESA+	972-5628	202.00	154.00	110.00
491	LT	14	DIL	Differential Driver and Receiver with Failsafe	LTC491CN#PBF	956-1390	545.00	347.00	280.00
491	LT	14	DIL	Differential Driver and Receiver with Failsafe	LTC491CN	386-2677	275.00	187.00	161.00
491	LT	14	DIL	Differential Driver and Receiver with Failsafe (IND TEMP)	LTC491IN	386-2689	338.00	230.00	198.00
491	LT	14	DIL	Differential Driver and Receiver with Failsafe (IND TEMP)	LTC491IN#PBF	956-1404	384.00	245.00	198.00
491	MAX	14	SOIC	RS485/RS422, Low Power Transmitter/Receiver with Receiver/Driver enable	MAX491CSD+	972-4567	137.00	105.00	75.00
491	MAX	14	SOIC	RS485/RS422, Low Power Transmitter/Receiver with thermal shutdown, Receiver/Driver enable, 2.5Mbps data rate for Duplex applications (IND TEMP)	MAX491ECSA+	972-4990	206.00	158.00	126.00
1080	LT	18	DIL	Dual RS232 Driver/Receiver with shutdown	LT1080CN#PBF	113-6636	316.00	203.00	165.00
1081	LT	16	DIL	Dual RS232 Driver/Receiver	LT1081CN	407-306	268.00	182.00	162.00
1081	LT	16	DIL	Dual RS232 Driver/Receiver	LT1081CN#PBF	955-9710	286.00	182.00	147.00
1133	LT	24	DIL	Enhanced, Low Power, RS232 Driver/Receiver. 3 Drivers/5 Receivers (enhanced LT1133CN)	LT1133ACN	459-770	409.00	295.00	266.00
1133	LT	24	DIL	Enhanced, Low Power, RS232 Driver/Receiver. 3 Drivers/5 Receivers (enhanced LT1133CN)	LT1133ACN#PBF	956-0114	459.00	293.00	236.00
1134	LT	24	DIL	Enhanced, Low Power, Quad RS232 Driver/Receiver	LT1134ACN	459-781	394.00	284.00	257.00
1134	LT	24	DIL	Enhanced, Low Power, Quad RS232 Driver/Receiver	LT1134ACN#PBF	956-0122	448.00	286.00	230.00
1180	LT	18	DIL	Enhanced, Low Power, Dual RS232 Driver/Receiver with shutdown	LT1180ACN	459-756	260.00	188.00	170.00
1180	LT	18	DIL	Enhanced, Low Power, Dual RS232 Driver/Receiver with shutdown	LT1180ACN#PBF	956-0246	296.00	189.00	152.00
1180	LT	18	SOIC	Low Power RS232 dual driver/receiver with 0.1 μ f capacitors	LT1180ACSW	386-2150	288.00	196.00	169.00
1180	LT	18	SOIC	Low Power RS232 dual driver/receiver with 0.1 μ f capacitors	LT1180ACSW#PBF	956-0254	328.00	209.00	169.00
1180	LT	18	DIL	Low Power RS232 dual driver/receiver with 0.1 μ f capacitors	LT1180AIN#PBF	113-6618	338.00	217.00	176.00
1181	LT	16	DIL	Enhanced, Low Power, Dual RS232 Driver/Receiver	LT1181ACN	459-768	260.00	188.00	170.00
1181	LT	16	DIL	Enhanced, Low Power, Dual RS232 Driver/Receiver	LT1181ACN#PBF	956-0262	278.00	178.00	143.00
1181	LT	16	SOIC	Enhanced, Low Power, Dual RS232 Driver/Receiver	LT1181ACSW	573-346	288.00	196.00	175.00
1181	LT	16	SOIC	Enhanced, Low Power, Dual RS232 Driver/Receiver	LT1181ACSW#PBF	956-0270	328.00	209.00	169.00
1348	LT	28	SOIC	Low Power RS232 Transceiver	LTC1348CSW#PBF	956-1064	481.00	316.00	257.00
1384	LT	18	DIL	Low Power, Dual RS232 Driver/Receiver, with Active in Shutdown mode.	LTC1384CN	638-330	366.00	272.00	238.00
1384	LT	18	DIL	Low Power, Dual RS232 Driver/Receiver, with Active in Shutdown mode.	LTC1384CN#PBF	956-1072	416.00	266.00	214.00
1384	LT	18	SOIC	5V low Power RS232 Transceiver with active receivers in shutdown mode	LTC1384CSW	386-2010	366.00	264.00	238.00
1384	LT	18	SOIC	5V low Power RS232 Transceiver with active receivers in shutdown mode	LTC1384CSW#PBF	956-1080	416.00	266.00	214.00
1385	ADI	20	SSOP	Low Power, 3.3V Dual RS232, Transceiver with Driver Disable Mode and Complete Shutdown	ADM1385ARSAZ	960-3654	123.00	102.00	82.00
1386	LT	16	SOIC	Low Power EIA/TIA562 Transceiver	LTC1386CS	476-7640	316.00	215.00	192.00
1386	LT	16	SOIC	Low Power EIA/TIA562 Transceiver	LTC1386CS#PBF	956-1099	316.00	203.00	165.00
1387	LT	20	SOIC	RS232/RS485 Multiprotocol Transceiver	LTC1387CSW	476-7652	479.00	326.00	281.00
1387	LT	20	SOIC	RS232/RS485 Multiprotocol Transceiver	LTC1387CSW#PBF	956-1102	479.00	326.00	290.00
1480	LT	8	DIL	3.3V Ultra-low Power RS485 Transceiver	LTC1480CN8	386-2550	268.00	193.00	175.00
1480	LT	8	DIL	3.3V Ultra-low Power RS485 Transceiver	LTC1480CN8#PBF	113-6631	268.00	172.00	140.00
1480	MAX	8	DIL	3.3V Ultra-low Power RS485 Transceiver (IND TEMP)	LTC1480IN8	386-2562	324.00	234.00	211.00
1480	MAX	28	DIL	Complete Isolated RS485/RS422 data interface with Transceiver, opto-couplers and transformer	MAX1480ACPI	305-2291	1,604.00	1,194.00	852.00
1480	MAX	28	DIL	Complete Isolated RS485/RS422 data interface with Transceiver opto-couplers and transformer (half duplex with 250kbps data range)	MAX1480BCPI	353-4029	1,533.00	1,141.00	814.00
1481	LT	8	DIL	CMOS, Ultra Low Power, RS485 Driver/Receiver with shutdown	LTC1481CN8	569-112	156.00	112.00	101.00
1481	LT	8	DIL	CMOS, Ultra Low Power, RS485 Driver/Receiver with shutdown	LTC1481CN8#PBF	113-6638	156.00	100.00	81.00
1483	LT	8	DIL	CMOS, Ultra Low Power, RS485 Driver Receiver with controlled slew rate, low EMI emission and shutdown	LTC1483CN8#PBF	956-1226	166.00	106.00	85.00
1483	LT	8	SOIC	Low Power RS485 Low EMI Transceiver with Shutdown	LTC1483CS8	476-7720	190.00	129.00	112.00
1483	LT	8	SOIC	Low Power RS485 Low EMI Transceiver with Shutdown	LTC1483CS8#PBF	956-1234	190.00	122.00	99.00
1483	LT	8	DIL	Ultralow Power RS485 Low EMI Transceiver with Shutdown (IND TEMP)	LTC1483IN8	386-2586	204.00	147.00	133.00
1483	LT	8	DIL	Ultralow Power RS485 Low EMI Transceiver with Shutdown (IND TEMP)	LTC1483IN8#PBF	956-1242	232.00	148.00	119.00
1483	MAX	8	DIL	CMOS, Ultra-low-power, RS-485/RS-422 Transceiver with limited slew rate, low EMI and shutdown	MAX1483CPA	301-1987	137.00	105.00	84.00
1483	MAX	8	DIL	CMOS, Ultra-low-power, RS-485/RS-422 Transceiver with limited slew rate, low EMI and shutdown	MAX1483CPA+	972-3870	173.00	132.00	94.00
1483	LT	8	DIL	CMOS, Ultra Low Power, RS485 Driver Receiver with controlled slew rate, low EMI emission and shutdown	LTC1483CN8	569-124	156.00	112.00	101.00
1485	LT	8	DIL	Low-Power Differential Bus/Line Transceiver	LTC1485CN8	476-7731	169.00	115.00	99.00
1485	LT	8	DIL	Low-Power Differential Bus/Line Transceiver	LTC1485CN8#PBF	956-1250	169.00	108.00	88.00
1485	NSC	8	SOIC	5V Low Power RS-485 Differential Bus Transceiver	LMS1485M	949-0701	123.00	87.00	64.00
1486	MAX	10	SOIC	CMOS, Software-selectable, RS-485/RS-422 Transceiver with limited slew rate and shutdown mode	MAX1486CUB+	972-3889	170.00	130.00	93.00
1487	NSC	8	SOIC	5V Low Power RS-485 / RS-422 Differential Bus Transceiver	LMS1487CM.	580-1084	126.00	90.00	65.00
1487	NSC	8	SOIC	5V Low Power RS-485 / RS-422 Differential Bus Transceiver	LMS1487CM	949-0710	126.00	90.00	65.00
1487	LT	8	DIL	CMOS, Ultra Low Power, RS485 Driver/Receiver as LTC1483CN8, with high impedance receiver inputs	LTC1487CN8	569-136	156.00	112.00	101.00
1487	NSC	8	DIL	5V Low Power RS-485 / RS-422 Differential Bus Transceiver	LMS1487CNA.	580-1096	131.00	93.00	68.00