Farnell

Anaerobic Sealants

Pipe Seal - 577



- Instant low pressure seal
- Suitable for coarse pipe threads and fitting up to R3"
- Withstands burst pressure of pipe when fully cured
- Meets BS6956 type A for gas sealing
- Suitable for drinking water

	Mftrs.				Price Each	1	
	List No.	Order Code	1+	5+	10+	50+	100+
50ml	0113092	702-3947					

Hydraulic Seal - 542



- Used for hydraulic and pneumatic systems
- Replaces tapes, pastes and compression fittings
- Meets **BS6956 type A** for gas sealing
- Medium strength
- Medium viscosity

	Mftrs.			1	Price Eacl	1	
	List No.	Order Code	1+	5+	10+	50+	100+
50ml	0113052	702-0855					

Multigasket - 574

LOCTITE.



- General purpose flange sealant
- Thixotropic Produces high pressure seal resisting to 50 bar
- Fills gaps to 0.5mm
- Operating temperature of 150°C

	Mftrs.	Price Each						
	List No.	Order Code	1+	5+	10+	50+	100+	
50ml	0511062	702-3741						

Contact Adhesives

Contact Adhesive - 528





- One part polychloroprene rubber/resin contact adhesive
- General Purpose
- Good temperature resistance
- High shear strength
- Easy to apply
- Ideal for bonding decorative laminated sheets, PVC to wood, wood composite board and metal
- Unsuitable for expanded polystyrene and bituminous surfaces

Warning: Flammable contents, do not use near any source of ignition, use in well ventilated area

					CHM	212
			Price	Each		
	Order Code	1+	12+	24+	48+	
1 Litre 2.5 Litre	704-4100 704-4112					
2.5 Litte	704-4112					J

Contact Adhesive - TX 528





- Thixotropic Contact adhesive
- Ideal for vertical and the underside of horizontal surfaces
- Excellent final bond strength

Ideal for bonding decorative laminates, rigid PVC, wood, chipboard, hardboard, cork, leather, rubber, stone and dense firm fabrics such as carpets

							ad	h4
				Price	Each			
	Order Code	1+	12+	24+	48+	96+	192+	
2.5 Litre	704-4148							

Impact Adhesive

KEVO-STIK



• An impact adhesive ideal for plastic laminates, wood, leather, rubber, metals, fab-

Flammable contents, do not use near any source of ignition, use in a well ventilated area

Please check with Sales Office for availability

			-	CF	1M60
			Price Each		
	Order Code	1+	12+	48+	
37ml Tube	.101-662				
		1+	6+	12+	
250ml Tin	101-661				
500ml Tin	.101-660				

Bostik C

Bostik Black, general pur-

- pose rubber to metal adhesive Good aging properties
- Suitable for rubber, cork, felt, linoleum, metal, wood and concrete

Warning:- Flammable contents, do not use near any source of ignition, use in a well ventilated area

Please check with Sales Office for availability

Price Fach **Order Code** 12+ 24+ 48+ 100ml 721-9210 721-9222 1 litre 5 litre

General Purpose - 1782 **Nitrile Adhesive**

Bostik



- General purpose nitrile based adhesive Clear adhesive
- Good chemical and temperature resis-
- Ideal for leather, wood, metal, PVC and a range of polymers

Warning:- Flammable contents, do not use near any source of ignition, use in a well ventilated area

Please check with Sales Office for availability

			Price Each		
Order Code	1+	6+	12+	24+	48+
100ml 721-9260 250ml 721-9271 1 litre 721-9283					