

Solid Wire Size mm <sup>2</sup>	Stud Size	ØA	ØB	C	D	F	G	Weight Kg/100	Mftrs. List No.	Order Code
2.5	4	4.3	2.3	7.5	4	13	1.2	0.13	T2.5-4	745-820
4	6	6.5	3	10	6.5	19	1.2	0.24	T4-6	745-832
6	5	5.3	3.8	8.5	6.5	24	1.5	0.31	T6-5	745-844
6	6	6.4	3.8	8.5	7.5	24	1.5	0.30	T6-6	745-856
10	6	6.4	4.5	9	7.5	27	1.5	0.36	T10-6	745-868
10	8	8.4	4.5	13	10	27	1.3	0.39	T10-8	745-870
10	10	10.5	4.5	17	12	27	1.5	0.37	T10-10	745-881
16	6	6.4	5.5	13	7.5	36	2.5	1.18	T16-6	745-893
16	8	8.4	5.5	13	10	36	2.5	1.18	T16-8	745-900
16	10	10.5	5.5	17	12	36	2.5	1.20	T16-10	745-911
25	6	6.4	7	14	7.5	38	3	1.49	T25-6	745-923
25	8	8.4	7	16	10	38	3	1.57	T25-8	745-935
25	10	10.5	7	17	12	38	3	1.58	T25-10	745-947
25	12	13	7	19	13	38	3	1.54	T25-12	745-959
35	8	8.4	8.2	17	10	42	3.5	2.75	T35-8	745-960
35	10	10.5	8.2	19	12	42	3.5	2.85	T35-10	745-972
50	8	8.4	10	20	10	52	4	4.5	T50-8	745-984
50	10	10.5	10	22	12	52	4	4.5	T50-10	745-996
70	10	10.5	11.5	24	12	55	4.5	6.15	T70-10	746-009
95	10	10.5	13.5	28	12	65	5	9.15	T95-10	746-010

CS425X

10 Per Pack		Price Per Pack				
Wire Size mm <sup>2</sup>	Stud Size	Order Code	1+	10+	25+	50+
2.5	4	745-820				
4	6	745-832				
6	5	745-844				
6	6	745-856				
10	6	745-868				
10	8	745-870				
10	10	745-881				
16	6	745-893				
16	8	745-900				
16	10	745-911				
25	6	745-923				
25	8	745-935				
25	10	745-947				
25	12	745-959				
35	8	745-960				
35	10	745-972				
50	8	745-984				
50	10	745-996				
70	10	746-009				
95	10	746-010				

## Hydraulic Crimping Tool Hand Operated



Tool H = 180 W = 216 D = 49  
Carrying Case H = 260 W = 345 D = 89

Best value

- Compact tool + case
- 35KN Crimping force
- Crimp stroke 5-8mm
- Die sets interchangeable in seconds
- Handy carrying case for tool and up to 10 die sets
- Ideal for off site use (no power source required)
- Crimp head rotates 360° for easy access
- Can be released part way through crimp cycle
- Audible "Click" on full crimp pressure

FOR SUITABLE CRIMP TERMINALS SEE BELOW

CS426X

Mftrs. List No.	Order Code	1+	3+	Price Each
D36	.745-686			

### Call for Latest Pricing

Products on this page may be subject to price changes in line with market trends. Call us for an update on (65) 788 0200.

## Die Sets

6, 10, 16, 25, 35, 50, 70, 95mm<sup>2</sup>



- 8 sizes from 6-95mm<sup>2</sup>
- Hexagonal style crimp
- Crimp sizes stamped on die sides easily visible when in crimp tool
- Crimp size embossed on copper tube during crimping
- Hardened steel die jaws
- Die sets interchangeable in seconds

CS428X

Crimp size mm <sup>2</sup>	Order Code	Crimp size mm <sup>2</sup>	Order Code	
6	.745-704	35	745-741	
10	.745-716	50	745-753	
16	.745-728	70	745-765	
25	.745-730	95	745-777	
		1+	3+	10+
All Order Codes				

## Crimp Tool for Copper Tube Terminals

DAVICO



Hexagon crimp

A high quality tool for crimping copper tube terminals with hexagon profile. A revolving die enables wire sizes between 6mm<sup>2</sup> and 50mm<sup>2</sup> to be easily crimped with minimal operator force. During the crimping process the solid core wire size is indented in the terminal to verify correct usage, ie, 6, 10, 16, etc. Metal body with black finish and rubber handles.

Mftrs. List No. DHC 50H

CS429X

Order Code	1+	5+	10+	25+	Price Each
269-062					

### Call for Latest Pricing

Products on this page may be subject to price changes in line with market trends. Call us for an update on (65) 788 0200.

### Total Customer Care

Our aim is to ensure you are 100% satisfied. If you ever have a query with your order, call us on (65) 788 0200