

## International Mains Leads

### Europe, 'Schuko', 2.5m



Cable length = 2.5m, Diameter = 6.9—7.2  
Free end stripped = 40, Conductors bared = 10

- Non-rewireable Schuko plug with dual earthing system, for use across the majority of Europe
- The plug complies with CEE7 sheet VII, approvals VDE, IMQ, NF-USE, OVE, KEMA-KEUR, FI, SEMKO, NEMKO, and DEMKO
- Harmonised 2.5 metre of 1.0mm<sup>2</sup> to CENELEC H021
- 10A free socket complies with EN60.320, has same approvals as the plug plus SEV

Current rating 10A @ 250V ac Plug contacts Brass, nickel plated  
Cable and connector housings Black PVC Socket contacts Phosphor bronze

FOR REWIREABLE EUROPEAN MAINS PLUGS, SEE PAGE 387

	Price Each					
Order Code	1+	25+	50+	100+	250+	500+
IEC socket	.210-699					
Bared ends	285-663					

### Switzerland, 2.5m



- Non-rewireable lead for use in Switzerland
- Plug complies with Swiss standard ASE1011(1959)Type 12
- 2.5 metres of 1.0mm<sup>2</sup> cable

Current rating 10A @ 250V ac Plug contacts Brass, nickel plated  
Cable and connector housings Black PVC Socket contacts Phosphor bronze

	Price Each					
Order Code	1+	25+	50+	100+	250+	500+
525-583.						

### Italy, 2.5m



- A non-rewireable lead for use in Italy
- Plug complies with Italian standard CEI 23-16
- 2.5 metres of 1.0mm<sup>2</sup> cable

Current rating 10A @ 250V ac Plug contacts Brass, nickel plated  
Cable and connector housings Black PVC Socket contacts Phosphor bronze

	Price Each					
Order Code	1+	25+	50+	100+	250+	500+
525-560.						

### Denmark, 2.5m



- Non-rewireable lead for use in Denmark
- Plug complies with Danish standard SRAF1962
- 2.5 metres of 1.00mm<sup>2</sup> cable

Current rating 10A @ 250V ac Plug contacts Brass, nickel plated  
Cable and connector housings Black PVC Socket contacts Phosphor bronze

	Price Each					
Order Code	1+	25+	50+	100+	250+	500+
525-546.						

### North America, 2m



- Non-rewireable lead suitable for use in USA and Canada
- Plug complies with UL498 and CSA22.2 No. 42
- 2 metres of light duty 18 AWG SJT cable

Cable length = 2m, Diameter = 6.6—6.9

Current rating 10A @ 125V ac Plug contacts Brass, nickel plated  
Cable and connector housings Black PVC Socket contacts Phosphor bronze

FOR TWO PIN REWIREABLE MAINS PLUGS AND SOCKETS, SEE PAGE 387

	Price Each					
Order Code	1+	25+	50+	100+	250+	500+
.210-705.						

### Australia, 2.5m - PENCON



- A non-rewireable lead for use in Australia, New Zealand, Fiji, Papua New Guinea and ROC. The plug complies with AS3112-1990 and NZSS198-1967. Two and a half metres of 1.0mm<sup>2</sup> cable to harmonised code H05VV-F interconnect the moulded plug and 10A IEC free socket. The socket is approved to NEMKO, NF-USE, DEMKO, CEPEC, BSI, IMQ, VDE, SEV, KEMA-KEUR, FI, OVE, and SEMKO.

Cable length = 2.5m, Diameter = 6.9—7.2

Current rating 10A @ 250V ac Plug contacts Brass  
Cable and connector housings Black PVC Socket contacts Phosphor bronze

Mfrs. List No. 355360

	Price Each					
Order Code	1+	25+	50+	100+	250+	500+
428-796.						

## Through Panel Mains Connector

### HARAX®



- IDC Technology
- Standard Pg13.5 fitting
- Quick and easy assembly
- Rated to IEC529/EN 60 529/DIN VDE 0470-1
- Flammability UL94V-0
- Sealed to IP67
- 4.8mm Faston or solder terminals on inside of case

Contacts Copper alloy, tin over nickel plated Mounting Hole 20.8-03.mm  
Insulation Black Polyamide Thread Pg 13.5  
Faston contacts 4.8 0.8mm Width across flats 24mm  
Suitable cable Cross section 0.75-1.5mm  
Insulation PVC/PE/PUR  
Wire diameter <2.8mm  
Outside diameter 5.6-8.5mm

Mfrs. List No. 2101-130-1013 = 307-4286, 2101-130-1023 = 307-4298,  
2101-000-0007 = 307-4304, 2101-000-0001 = 307-4316

	Price Each				
Description	Order Code	1+	10+	25+	50+
Connector with faston	307-4286				
Connector with solder lugs	307-4298				
Plastic nut to mount contact carrier	307-4304				
Socket wrench	307-4316				

## IEC Free Sockets

### Rewireable Free Sockets



H = 18.4, W = 26.4  
D = 78.3 (inc. sleeve)

H = 18.4,  
W = 65 (inc sleeve)  
D = 51.9

- Rewireable, line socket style connectors, complies with BS4491
- Internal screw terminations and strain relief
- Approvals: EN60.320, UL, CSA, VDE, BS, SEV, SEMKO, NEMKO, FEMKO, DEMKO and IMQ

Contact rating 10A @ 250V ac Housing Black nylon, UL94V-0  
Contacts Brass nickel plated

Mfrs. List No. PX0587 = 313-713, PX0587SE = 313-725

FOR SUITABLE MAINS FLEX (1.0mm<sup>2</sup>) 3 CORE, SEE PAGE 116