

Corded Drills — continued

Variable 2-Speed, Reversing, 13mm Hammer, 1010W

Atlas Copco



Note: Industrial power tools are designed specially for the professional user and will give reliable service in industrial environments.

H = 230, W = 80, D = 370

- Variable 2 speed reversing hammer drill
- Fitted with the AEG Anti-Vibration System (AVS)
- The AVS cuts out 50% of vibration normally transmitted to the user
- AVS consists of internal rubber shock absorbers between gearbox and motor and a soft rubber inlay down the rear of the pistol grip
- Two speed synchromesh gearbox allows speed changing while drilling
- 7 settings to limit the maximum speed of the drill
- A table on top of the drill shows the best setting for drill size/speed/material
- Constant speed electronics maintain rpm under variable loads
- Handle has storage for 3 1/4" hex bits, small drill bits and the chuck key
- Supplied with carrying case

Max. drilling capacity	13mm steel	Rated speed:	Speed 1	0 to 970 rpm
	40mm wood		Speed 2	0 to 2850 rpm
Screwdriving capacity	24mm brick and tile	Percussion rate	45,600/min.	
	20mm concrete		Drill chuck thread	1/2" 20 UNF
Power input	wood up to 8mm ∅	Weight	2.7kg	
	1010W			

TPA23X

	Order Code	1+	3+	6+
PD2E24RS 230V	282-479			

Drill/Chisel SDS-plus Pneumatic Hammer, 620W Industrial Standard

BOSCH



Note: Industrial power tools are designed specifically for the professional user and will give reliable service in industrial environments.

H = 205, W = 80, D = 355

- Variable speed and trigger lock for continuous operation
- Features rotation stop, enabling the hammer action to work without the bit rotating
- The bit can be replaced with a chisel to allow the tool to be used as a power chisel
- Chisels are suitable for work in plaster, rendering or brickwork
- The chisel can be locked in any one of 36 operating positions
- Mode selection has 4 positions, plain non-hammer drilling, hammer drilling, chisel angle select and chisel operation
- Selector switch has positive lock to avoid accidental switching
- Features a safety clutch, depth gauge, steadying handle and case

Drilling diameters		Power output	360W
Masonry	24mm	Speed	0 to 820rpm
Steel	13mm	Impact rate	0 to 4850/min
Wood	30mm	Weight	2.4kg
SDS-Bits	4 to 24mm	Manufacturers List No.	GBH2000
Power input	620W		

TPA35X

	Order Code	1+	3+	6+
230V ac drill	457-942			
110V ac drill	457-954			
Chisels				
Point	457-966			
Standard flat	457-978			
Gouge	457-991			

GBH 4 DFE multiDRILL Total Drilling System

BOSCH



- 4kg, 750W, SDS+ rotary hammer with variable speed switch
- Rotary drilling, hammer drilling and rotation stop for chiselling
- Soft grip handle designed to reduce vibration for user comfort
- Safety clutch prevents machine overload and injury, enables the use of diamond cores from 90mm to 152mm
- Supplied with additional keyless conventional chuck for straight shank bits
- Supplied complete with 3 SDS plus bits, 1 cold chisel, 1 wood chisel, 8 brad point wood bits, 3 flat wood bits, 19 HSS precision ground bits, 4 Multi purpose bits safety kit and carry case

Power Input	750W	Impact Rate	0-3900 bpm
No load Speed	0-650 rpm	Impact Force	3.5 Joule
		Weight	3.9 kg

tpa154

Mfrs. List No.	Order Code	1+	3+	6+
GBH4DFE 240V	725-6255			
GBH4DFE 110V	725-6267			

4Kg SDS Plus Multi Purpose Hammer Drill SUPERMAK

Makita
New



- 3 mode action
- Rotary, rotary hammer and hammer mode only modes available
- 30mm max. in concrete
- 90mm max core diameter
- Variable blows per minute: 1650 - 3300
- 360 - 720rpm
- 850 Watts
- 5.3 joules impact energy
- Service indicator lights

Standard equipment: 18 piece mixed bit set, 7 piece SDS + bit set, keyless drill chuck, chuck adaptor, cold chisel, scaling chisel, depth gauge, grease and carry case.

TPA198

Mfrs. List No.	Order Code	1+	3+	6+
SUPERMAK	329-4043			


Drill Accessories

90° Angle Head, SDS-Plus

BOSCH



Overall length = 140



- Greatly enhances the versatility of BOSCH SDS Plus hammer drills
- Will operate with or without the hammer action
- Allows variable speed drills to hammer drill, rotary drill or drive screws in confined areas
- Simply slips over the existing chuck and is tightened into place around the drill collar
- Suitable for drill bits from 5 to 20mm diameter

TPA97X

Mfrs. List No.	Order Code	1+	3+	6+
1618 580 000	202-551			