

EASY ACCESS WITHOUT KEYS

CL500

Heavy-duty mechanical locks with full size lever handles, allowing use as the primary lock on doors.

The CL500 range of mechanical locks offer a variety of options. Allows the user flexibility on how to manage entry – by key, code or 'code free' entry. Throwing the deadbolt on the mortice lock models will lock out the code users when appropriate. A safety feature ensures that the inside lever handle will retract the deadbolt so avoiding accidentally locking a person in the room. Front and back plates can be purchased for use with existing locks.

FEATURES

- Heavy-duty Codelock
- PVD low maintenance finish
- Full size lever handles
- 12 options available
- 2,047 non sequential codes available
- Code Free option available
- Mortice Latch and Mortice Lock functions
- Available in stainless steel or polished brass finish
- Suitable for internal and external use
- Limited lifetime guarantee*
- Codelocks Fire Kit Packs can be fitted to latch locks for 30 or 60 minute fire doors. Tested in accordance with BS EN 1634-1: 2008





CL500

Front and Back Plates

Front and back plates only for use with existing mortice latch or lock. The existing lock must have either a fixing hole 22mm (7/8") below follower (spindle) or two horizontal holes either side of the follower 38mm (1 1/2") centres.



CL510

Mortice Latch

Tubular mortice latch locks. Medium-duty stainless steel latchbolt head with 'anti-shim' deadlocking plunger, 8mm (5/16") follower. The outside lever handle will retract the latch after a correct code is entered. The spring loaded latchbolt will lock automatically when the door is closed.



CL520

Mortice Lock

Euro profile mortice sash lock with deadbolt and latchbolt. Complete with double cylinder to control deadbolt and to retract latchbolt. With the deadbolt locked it denies access to a code user. The split follower enables the inside lever to retract the deadbolt and latch to prevent accidental lock in when the deadbolt is thrown. Supplied with double Euro profile cylinders with three keys. The key will open the door for management functions.



Code Change Method

Requires removal of lock from door. Locks are supplied with a random code commencing with the 'C' clear button. To change the code after fitting, the lock must first be removed from the door. The code is non sequential, i.e. the code can be entered in any preferred order (e.g. 1234 can be 4321 or 1342). A total of 2,047 different codes are available - any of which can be entered in any order.

OPTIONS

Latch Options:

60mm (2 3/8") backset requires 25mm (1") hole, 82mm (3 1/4") deep.
70mm (2 3/4") backset requires 25mm (1") hole, 92mm (3 5/8") deep.

Code Free Option:

The outside lever will retract the latchbolt without using a code.

Back to Back Option (BB):

Two coded plates for installation on both sides of the door. Provides coded access in both directions.


Panic Kit Option (PK):

Extra long spindle provided to work with most single point panic pads or bars.


For further product model options see price list.

PRODUCT DIMENSIONS


CL500



CL510



CL520



TECHNICAL SPECIFICATIONS

| | |
|-----------------|---|
| Options | 12 available |
| Spindle Type | Two part 8mm (5/16") spring loaded spindle |
| Material | Zinc Alloy |
| Door Thickness | 35mm – 60mm (1 3/8" – 2 3/8") |
| Buttons | 12 stainless steel buttons |
| Non Handed | Locks will fit doors hung on the left or right |
| Fitting Options | Vertical |
| Finish | PVD (Physical Vapour Deposition) hardwearing low maintenance finishes SS (stainless steel) and PB (polished brass) |
| Codes | 2,047 non sequential codes available |
| Code Storage | Single Code |
| Standards | Codelocks Fire Kit Packs can be fitted to latch locks for 30 or 60 minute fire doors. Tested in accordance with: BS EN 1634-1:2008 |
| Suitable For | Internal and external use |

*Codelocks mechanical locks will be repaired, serviced or replaced free of charge if they develop a manufacturing fault. Faults caused by misuse, abuse and/or poor fitting are not covered by the guarantees.

