

3421612

ALL RIGHTS RESERVED. NO PORTION OF THIS PUBLICATION, WHETHER IN WHOLE OR IN PART CAN BE REPRODUCED WITHOUT THE EXPRESS WRITTEN CONSENT OF SPC TECHNOLOGY.

REVISIONS			DOC. NO. SPC-F004 • Effective: 12/21/98 • DCP No: 680					
DCP #	REV	DESCRIPTION	DRAWN	DATE	CHECKD	DATE	APPRVD	DATE
		NOT released	JWM	12/30/98				



High frequency replacement probe w/3-position switchable attenuation, x1, x10 and Ref. 250MHz @ -3dB x 10 position, 10M Ω impedance (1M Ω scope input), 14pF capacitance, <1.4ns risetime. 10MHz @ -3db x 1 position, 1M Ω impedance (scope input), 90pF capacitance, 35ns risetime. Ref position disconnects the probe tip and grounds the scope input. 1.2m cable length with low-noise compensation, 10-35pF, in BNC box. Probe meets EN61010-2-031, 600V (DC+AC peak) CATI P2. Accessory kit and storage pouch included.

SPC-F004.DWG

DISCLAIMER:
ALL STATEMENTS AND TECHNICAL INFORMATION CONTAINED HEREIN ARE BASED UPON INFORMATION AND/OR TESTS WE BELIEVE TO BE ACCURATE AND RELIABLE. SINCE CONDITIONS OF USE ARE BEYOND OUR CONTROL, THE USER SHALL DETERMINE THE SUITABILITY OF THE PRODUCT FOR THE INTENDED USE AND ASSUME ALL RISK AND LIABILITY WHATSOEVER IN CONNECTION THEREWITH.



DRAWN BY:	DATE:
JEFF MCVICKER	12/30/98
CHECKED BY:	DATE:
APPROVED BY:	DATE:

DRAWING TITLE: 250 MHz Oscilloscope Probe			
SIZE A	DWG. NO. 76-106	ELECTRONIC FILE 84N2148.dwg	REV
SCALE:	U.O.M.:	SHEET: 1 OF 1	