

8163 Paired - Low Capacitance Computer Cable for EIA RS-232/422 & Digital

 	<p>For more information please call 1-800-Belden1</p> <p><u>See Put-ups and Colors</u></p> <p>Related Documents : No. 3 for Paired Cables (Belden Standard).pdf</p>
----------------------------------------------------------------------------------------------------------------------------------------------------------------------	--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

Description:

24 AWG stranded (7x32) TC conductors, Datalene® insulation, twisted pairs individually Beldfoil® shielded + overall 100% Beldfoil + TC braid shield (65% coverage), drain wire, PVC jacket.

PHYSICAL CHARACTERISTICS:

CONDUCTOR:

Number of Pairs	3
Total Number of Conductors	6
AWG	24
Stranding	7x32
Conductor Material	TC - Tinned Copper

INSULATION:

Insulation Material Trade Name	Datalene®
Insulation Material	FPE - Foam Polyethylene
Lay Length	1 in.
Twists/ft.	12

Pair Color Code Chart :

Number	Color	Number	Color
1	Black & Red	3	Black & Green
2	Black & White		

INNER SHIELD:

Inner Shield Material Trade Name	Beldfoil® (Z-Fold®)
Inner Shield Type	Tape
Inner Shield Material	Aluminum Foil-Polyester Tape
Inner Shield % Coverage	100 %
Inner Shield Drain Wire AWG	24
Inner Shield Drain Wire Stranding	7x32
Inner Shield Drain Wire Conductor Material	TC - Tinned Copper

OUTER SHIELD:

8163 Paired - Low Capacitance Computer Cable for EIA RS-232/422 & Digital

Outer Shield Material Trade Name Beldfoil®

Outer Shield Type Tape/Braid

Outer Shield Material :

Layer Number	Material Trade Name	Type	Material	% Coverage (%)
1	Beldfoil®	Tape	Aluminum Foil-Polyester Tape	100
2		Braid	TC - Tinned Copper	65

Outer Shield % Coverage 100 %

OUTER JACKET:

Outer Jacket Material PVC - Polyvinyl Chloride

OVERALL NOMINAL DIAMETER:

Overall Nominal Diameter .359 in.

MECHANICAL CHARACTERISTICS:

Operating Temperature Range -40°C To +60°C

Non-UL Temperature Rating 60°C (UL AWM Style 2493)

Bulk Cable Weight 76 lbs/1000 ft.

Max. Recommended Pulling Tension 84 lbs.

Min. Bend Radius (Install) 3.75 in.

APPLICABLE SPECIFICATIONS AND AGENCY COMPLIANCE:

APPLICABLE STANDARDS:

NEC/(UL) Specification CM

CEC/C(UL) Specification CM

AWM Specification UL Style 2493 (300 V 60°C)

EU CE Mark (Y/N) Yes

EU RoHS Compliant (Y/N) Yes

EU RoHS Compliance Date (mm/dd/yyyy): 01/01/2004

FLAME TEST:

UL Flame Test VW-1, UL1685 UL Loading

PLENUM/NON-PLENUM:

Plenum (Y/N) N

ELECTRICAL CHARACTERISTICS:

Nom. Characteristic Impedance 100 Ohms

Nom. Capacitance Conductor to Conductor @ 1 KHz 12.5 pF/ft

Nom. Cap. Cond. to Other Cond. & Shield @ 1 KHz 22 pF/ft

Nominal Velocity of Propagation 78 %

Nom. Conductor DC Resistance @ 20 Deg. C 24.0 Ohms/1000 ft

Ind. Pair Nominal Shield DC Resistance @ 20 Deg. C 18 Ohms/1000 ft

8163 Paired - Low Capacitance Computer Cable for EIA RS-232/422 & Digital

Nominal Outer Shield DC Resistance @ 20 Deg. C	4.4 Ohms/1000 ft
Max. Operating Voltage - UL	300 V RMS
Max. Recommended Current	1.6 Amps per conductor @ 25°C

NOTES:

Notes	Datalene® insulation features include low dielectric constant and a dissipation factor for high-speed, low-distortion data handling. Physical properties include good crush resistance and light weight.
-------	----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

PUT-UPS AND COLORS:

Item	Description	Put-Up (ft.)	Ship Weight (lbs.)	Jacket Color	Notes
8163 060100	3 FS PR #24 FHDPE SH PVC	100	7	CHROME	
8163 0601000	3 FS PR #24 FHDPE SH PVC	1000	66	CHROME	C
8163 060500	3 FS PR #24 FHDPE SH PVC	500	34	CHROME	C

C = CRATE REEL PUT-UP.

Revision Number: 1 Revision Date: 07-25-2005

© Copyright 2006 Belden, Inc
All Rights Reserved.

Although Belden ("Belden") makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with the following environmental regulations: California Proposition 65 Consent Judgment For Wire & Cable Mfgs. (San Francisco Superior Court Nos. 312962 And 320342); EU RoHS (Directive 2002/95/EC, 27-Jan-2003); Material manufactured prior to the compliance date may still be in stock at Belden facilities and in our Distributor's inventory. EU ELV (Directive 2000/53/EC, 18-Sept-2000); EU WEEE (Directive 2002/96/EC, 27-Jan-2003); And EU BFR (Directive 2003/11/EC, 6-Feb-2003). The information provided in this Product Disclosure, and the identification of materials listed as reportable or restricted within the Product Disclosure, is correct to the best of Belden's knowledge, information and belief at the date of its publication. The information provided in the Product Disclosure is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.

Belden declares this product to be in compliance with EU LVD (Low Voltage Directive 73/23/EEC), as amended by directive 93/68/EEC.