

482.6 mm (19") installation

482.6 mm (19")/metric installation



Adaptor

for RNC

For installing 10" components in 296.2 mm (1 1/2 19") enclosures.

Material:
Sheet steel

Colour:
RAL 7035

U	Model No. DK
1	7870.760
4	7870.765



Spring nuts with screws

M5 x 10 mm/M6 x 10 mm for T-slot mounting angle

The spring nuts ensure flexible, secure mounting of accessory components on the T-slot of the FR(i) frame and on the T-slot mounting angles.

Supply includes:
50 spring nuts,
50 spring nuts, 10 mm, self-locking.

Design	Packs of	Model No. DK
Phillips-head, M6	50	7000.990
Multi-tooth 25, M5	50	7856.755



Assembly screws

M5 x 16 mm/M6 x 16 mm

For electronic equipment, 482.6 mm (19") installed components and blanking plates.

Supply includes:
Plastic washers.

Design	Packs of	Model No. EL
Phillips-head screw M5	100	2099.500
Cheese-head screw M6	100	2093.200
Phillips-head screw M6	100	2089.000



Multi-tooth screw

M5 x 16 mm/M6 x 16 mm

For optimum transmission of torques, an extended tool life and increased safety and reliability when tightening and loosening screw connections.

Supply includes:
Plastic washers.

	Bit size	Packs of	Model No. DK
M5	Multi-tooth 25	100	7094.500
M6	Multi-tooth 30	100	7094.600

482.6 mm (19")/metric installation

B
7.8