

**Ground terminal blocks
not electrically connected
to the mounting rail
(isolated ground)**

Compression clamp




DIN 1 - 3

For other terminal block accessories, see Product Guide pages for standard blocks of the same size.

MA 2,5/5.PI

Spacing 5 mm + 0,08 .200"



Type Part number

Yellow body with green strip on the top
MA 2,5/5.PI **0165 677.03**

IEC UL CSA

IEC	UL	CSA
NFC DIN	UL	CSA
Wire size	22-12 AWG	22-12 AWG
Compression clamp	22-12 AWG	22-12 AWG
Stranded wire	22-12 AWG	22-12 AWG

Short circuit current 300A/1s

Rated wire size / Gauge 2,5 mm² / A3 12 AWG 12 AWG

Other characteristics

Wire stripping length	Recomm. screwdriver	Recomm. torque	Protection
10 mm .39"	3.5 mm .14"	0,4-0,6 Nm 3.5-5.3 lb.in	IP 20 NEMA 1

Approvals


Accessories

Type	Part number
1 End section yellow FEM6 th. 2,8 mm	0103 062.21
2 Separator end section grey SCF6 th. 3 mm	0118 707.03

R See markers marking method (10) sides of block and only RC510, top of block

M 4/6.PI

Spacing 6 mm + 0,05 .238"



Type Part number

Yellow body with green strip on the top
M 4/6.PI **0165 275.00**

IEC UL CSA

IEC	UL	CSA
NFC DIN	UL	CSA
Wire size	22-10 AWG	22-10 AWG
Compression clamp	22-10 AWG	22-10 AWG
Stranded wire	22-10 AWG	22-10 AWG

Short circuit current 480A/1s

Rated wire size / Gauge 4 mm² / A4 10 AWG 10 AWG

Other characteristics

Wire stripping length	Recomm. screwdriver	Recomm. torque	Protection
9,5 mm .37"	4 mm .16"	0,5-0,8 Nm 4.4-7 lb.in	IP 20 NEMA 1

Approvals


Accessories

Type	Part number
1 End section yellow FEM6 th. 2,8 mm	0103 062.21
2 Separator end section grey SCF6 th. 3 mm	0118 707.03

R See markers marking method (11) (12)

M 4/6.3A.PI

Spacing 6 mm + 0,05 .238"



Type Part number

Yellow body with green strip on the top
M 4/6.3A.PI **0165 589.24**

IEC UL CSA

IEC	UL	CSA
NFC DIN	UL	CSA
Wire size	22-10 AWG	12 AWG max.
Compression clamp	22-10 AWG	12 AWG max.
Stranded wire	22-10 AWG	12 AWG max.

Short circuit current 480A/1s

Rated wire size / Gauge 4 mm² / A4 10 AWG 12 AWG

Other characteristics

Wire stripping length	Recomm. screwdriver	Recomm. torque	Protection
9,5 mm .37"	4 mm .16"	0,5-0,8 Nm 4.4-7 lb.in	IP 20 NEMA 1

Approvals

Accessories

Type	Part number
1 End section yellow FEM3A th. 3 mm	0103 862.20

R See markers marking method (11) (12)

**Ground terminal blocks
not electrically connected
to the mounting rail
(isolated ground)**

Compression clamp




DIN 1 - 3

For other terminal block accessories, see Product Guide pages for standard blocks of the same size.

M 4/6.4A.PI

Spacing 6 mm + 0,05 .238"



Type Part number

Yellow body with green strip on the top
M 4/6.4A.PI **0165 590.21**

IEC UL CSA

IEC	UL	CSA
NFC DIN	UL	CSA
Wire size	22-10 AWG	12 AWG max.
Compression clamp	22-10 AWG	12 AWG max.
Stranded wire	22-10 AWG	12 AWG max.

Short circuit current 480A/1s

Rated wire size / Gauge 4 mm² / A4 10 AWG 12 AWG

Other characteristics

Wire stripping length	Recomm. screwdriver	Recomm. torque	Protection
9,5 mm .37"	4 mm .16"	0,5-0,8 Nm 4.4-7 lb.in	IP 20 NEMA 1

Approvals

Accessories

Type	Part number
1 End section yellow FEM4A th. 3 mm	0103 863.21

R See markers marking method (11) (12)