## IEC Appliance Plug F shuttered, 70°C



4721











## Description

- Panel Mount Screw-on from front side
- Outlet shuttered, Protection class I, Pin temperature 70 °C
- Solder terminals or quick connect terminals

# Other versions on request

- For protection class II

#### Weblinks

Approvals: http://www.schurter.com/approvals RoHS: http://www.schurter.com/rohs


Technical Data			
Ratings IEC	10 A / 250 VAC; 50 Hz		
Ratings UL/CSA	15 A / 250 VAC; 60 Hz		
Dielectric Strength	> 2 kVAC between L-N		
	> 2 kVAC between L/N-PE		
	(1 min/50 Hz)		
Allowable Operation Temp.	-25 °C to 70 °C		
Degree of Protection	from front side IP 30 acc. to IEC 60529		
Protection Class	Suitable for appliances with protection		
	class I acc. to IEC 61140		
Terminal	Solder terminals or quick connect termi-		
	nals		
Panel Thickness s	Screw-on: max 8 mm		
	Mounting screw torque max 0.5 Nm		
Material: Housing	Thermoplastic, black, UL 94V-0		


Appliance-Inlet /-Outlet	F acc. to IEC/EN 60320-2-2,
	UL 498, CSA C22.2 no. 42 (for cold con-
	dition) pin-temperature 70 °C, 10 A, Pro-
	tection class I


**Dimensions** 4721

Length |

49 mm







Shutter operation: shutters opened by plug insertion Shutter operation: shutters closed when plug is removed

- E: Solder terminals 3.5 x 0.8 mm<TAB/><TAB/>28.4 mm
- E: Quick connect terminals 4.8 x 0.8 mm<TAB/>31.1 mm
- E: Quick connect terminalse 6.3 x 0.8 mm<TAB/>33.2 mm



#### Variants

Туре	Panel mounting	Panel Thickness s [mm]	Terminal	Order Number
4721	Screw-on	-	Quick connect terminals 4.8 x 0.8 mm	4721.0100
4721	Screw-on	-	Quick connect terminals 6.3 x 0.8 mm	4721.0000
4721	Screw-on	-	Solder terminals 3.8 x 0.8 mm	4721.0300

Class II product also available on request

Cord retaining clamps and insulation covers see accessories

Packaging unit 100 Pcs

## Accessory

## Description



**Assorted Covers** 



Cord retaining kits