



1. MAX. PANEL THICKNESS=5mm

- NOTES: FINISH (PLATING THICKNESS IN MICRO-INCHES)
1. BRASS PER QQ-B-626
 2. BRASS PER QQ-B-613
 3. NICKEL PL. 100 MIN. THICK OVER ZINC ALLOY
 4. TIN PLATING
 5. PHOSPHOR BRONZE PER QQ-B-750
 6. GOLD FLASH OVER NICKEL PL. 50 MIN. THICK AT MATING AREA.
 7. TIN-LEAD PL. 100 MIN. THICK OVER NICKEL PL. 50 MIN. THICK AT TAIL.
 8. ZINC DIECAST
 9. POLYPROPYLENE UL 94HB
 10. PBT (UL 94 V-0)

| NO. | DESCRIPTION | MATERIAL | FINISH | Q'TY | DRAWING NO. |
|-----|---------------|----------|--------|---------|-------------|
| 8 | HEX NUT | | NOTE 1 | NOTE 3 | |
| 7 | LOCK WASHER | | NOTE 2 | NOTE 3 | |
| 6 | MOUNTING POST | | NOTE 2 | NOTE 4 | |
| 5 | POST | COPPER | | NOTE 4 | |
| 4 | CONTACT PIN | | NOTE 5 | NOTE 6 | |
| 3 | INSULATOR | | NOTE 8 | NATURAL | |
| 2 | BODY | | NOTE 7 | NOTE 3 | |
| 1 | HOUSING | | NOTE 9 | WHITE | |

| | | | | | |
|---------------------------------------|--------|--|--|----------------------------|-----------|
| DIMENSIONS ARE IN MILLIMETERS | | | | PART NO. B6252H5-NPP3G-75T | |
| UNLESS OTHERWISE SPECIFIED TOLERANCES | | | | APPROVED | DATE |
| 0.5-6 | = ±0.2 | | | | 10-11-01' |
| 6-30 | = ±0.4 | | | CHECKED | DATE |
| 30-120 | = ±0.6 | | | | 10-11-01' |
| 120-315 | = ±1 | | | DRAWN | DATE |
| 315-1000 | = ±1.6 | | | | 10-11-01' |
| 1000-2000 | = ±2.4 | | | FILE NO. | |

Amphenol

TITLE
BNC R/A PC MOUNT RECEPT. JACK

DRAWING NO.

ITEM NO.