


multicomp	PART NO.			REVISIONS						
		ECN #	REV	DESCRIPTION	DRAWN	DATE	CHECKD	DATE	APPRVD	DATE
	4409A-08	-	Α		Geetha	24/4/08	Suresh	24/4/08	G. C	09/5/08

F







Dimensions : Millimetres

Specifications:

•	
Current rating	: 1.0A ac/dc.
Voltage rating	: 30V ac/dc.
Maximum contact resistance	: 20m ohm.
Minimum insulation resistance	: 1000M ohm
Withstanding voltage	: 500V ac for
Operating temperature range	: -40°C to +10
Material and Finish	
Insulator	: High tempat
Contact	: Copper allo
Plating	: Selective pla

30V ac/dc. 20m ohm.

- 1000M ohm.
- 500V ac for one minute.
- -40°C to +105°C.
- High tempature plastic.
- Copper alloy.
- Selective plated.

Engineering Dimension


Circuits	Dimension A	Dimension B
8	13.53	7.62

Dimensions : Millimetres

(the 'caroup') or are licensed to it. No licence is granted for the use or it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change with- out notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the prod- ucts for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or	TOLERANCES:	DRAWN BY:	DATE:	DRAWI	NG TITLE:				
	UNLESS OTHERWISE SPECIFIED, DIMENSIONS ARE FOR REFERENCE PURPOSES ONLY.	Geetha	24/04/08]	Male Connector - 8 Way				
		CHECKED BY:	DATE:	SIZE	DWG NO.		ELECTRONIC FILE 4409 3 DWG		REV
		Suresh	24/04/08			M10000878			A
		APPROVED BY:	DATE:						
		G.Cook	09/05/08	SCALE: NTS		U.O.M.: mm		SHEET: 1	OF 2

	PART NO.	REVISIONS									
		ECN #	REV	DESCRIPTION	DRAWN	DATE	CHECKD	DATE	APPRVD	DATE	
	4409A-08	-	А	RELEASED	Geetha	24/4/08	Suresh	24/4/08	G. C	09/5/08	

Recommended PCB Layout




Dimensions : Millimetres

Part Number Table

Description	Part Number
Connector Male, 8 Way	4409A-08

Part Number Explanation:



Number of Contact : 08 = 8 contacts

This data sheet and its contents (the "Information") belong to the Premier Farnell Group (the "Group") or are licensed to it. No licence is granted for the use of it other than for	TOLERANCES:	DRAWN BY:	DATE:	DRAWING TITLE:				
information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change with- out notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the prod- ucts for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or	UNLESS OTHERWISE	Geetha	24/04/08	Male Connector - 8 Way				
	SPECIFIED, DIMENSIONS ARE FOR REFERENCE PURPOSES ONLY.	CHECKED BY:	DATE:	SIZE DWG NO.		ELECTRONIC FILE	REV	
		Suresh	24/04/08	Δ	M10000878	4409_3_DWG	A	
		APPROVED BY:	DATE:					
		G.Cook	09/05/08	SCALE: NTS	U.O.M.: mm	SHEET: 2 O	DF 2	