



9537 Non-Paired - Computer Cable for EIA RS-232 Applications

| | |
|--|--|
|   | <p>For more information please call 1-800-Belden1</p> <p><u>See Put-ups and Colors</u></p> <p>Related Documents : No. 1.pdf</p> |
|--|--|

Description:

24 AWG stranded (7x32) tinned copper conductors, conductors cabled, semi-rigid PVC insulation, overall Beldfoil® shield (100% coverage), 24 AWG stranded tinned copper drain wire, PVC jacket.

PHYSICAL CHARACTERISTICS:

CONDUCTOR:

| | |
|----------------------------|--------------------|
| Number of Conductors | 7 |
| Total Number of Conductors | 7 |
| AWG | 24 |
| Stranding | 7x32 |
| Conductor Material | TC - Tinned Copper |

INSULATION:

| | |
|--------------------------------|--------------------------|
| Insulation Material | PVC - Polyvinyl Chloride |
| Nom. Insulation Wall Thickness | .010 in. |

OVERALL CABLING:

| | |
|----------------------------|----------|
| Overall Cabling Lay Length | 1.75 in. |
|----------------------------|----------|

Overall Cabling Color Code Chart :

| Number | Color | Number | Color |
|--------|-------|--------|--------|
| 1 | Black | 5 | Brown |
| 2 | White | 6 | Blue |
| 3 | Red | 7 | Orange |
| 4 | Green | | |

OUTER SHIELD:

| | |
|--|------------------------------|
| Outer Shield Material Trade Name | Beldfoil® |
| Outer Shield Material | Aluminum Foil-Polyester Tape |
| Outer Shield % Coverage | 100 % |
| Outer Shield Drain Wire AWG | 24 |
| Outer Shield Drain Wire Stranding | 7x32 |
| Outer Shield Drain Wire Conductor Material | TC - Tinned Copper |



9537 Non-Paired - Computer Cable for EIA RS-232 Applications

OUTER JACKET:

| | |
|-------------------------------------|--------------------------|
| Outer Jacket Material | PVC - Polyvinyl Chloride |
| Outer Jacket Nominal Wall Thickness | .032 in. |

OVERALL NOMINAL DIAMETER:

| | |
|--------------------------|----------|
| Overall Nominal Diameter | .209 in. |
|--------------------------|----------|

MECHANICAL CHARACTERISTICS:

| | |
|----------------------------------|--------------------------|
| Operating Temperature Range | -30°C To +80°C |
| UL Temperature Rating | 80°C (UL AWM Style 2464) |
| Bulk Cable Weight | 27.4 lbs/1000 ft. |
| Max. Recommended Pulling Tension | 38.5 lbs. |
| Min. Bend Radius (Install) | 2.12 in. |

APPLICABLE SPECIFICATIONS AND AGENCY COMPLIANCE:

APPLICABLE STANDARDS:

| | |
|---------------------------------------|----------------------------|
| NEC/(UL) Specification | CMG |
| CEC/C(UL) Specification | CMG |
| AWM Specification | UL Style 2464 (300 V 80°C) |
| EU CE Mark (Y/N) | Yes |
| EU RoHS Compliant (Y/N) | Yes |
| EU RoHS Compliance Date (mm/dd/yyyy): | 04/01/2005 |

FLAME TEST:

| | |
|------------------|-----|
| C(UL) Flame Test | FT4 |
|------------------|-----|

PLENUM/NON-PLENUM:

| | |
|--------------|---|
| Plenum (Y/N) | N |
|--------------|---|

ELECTRICAL CHARACTERISTICS:

| | |
|---|--------------------------------|
| Nom. Capacitance Conductor to Conductor @ 1 KHz | 33 pF/ft |
| Nom. Cap. Cond. to Other Cond. & Shield @ 1 KHz | 65 pF/ft |
| Nom. Conductor DC Resistance @ 20 Deg. C | 25 Ohms/1000 ft |
| Nominal Outer Shield DC Resistance @ 20 Deg. C | 18 Ohms/1000 ft |
| Max. Operating Voltage - UL | 300 V RMS (UL AWM Style 2464) |
| Max. Recommended Current | 1.75 Amps per conductor @ 25°C |

PUT-UPS AND COLORS:

| Item | Description | Put-Up (ft.) | Ship Weight (lbs.) | Jacket Color | Notes |
|-------------|------------------|--------------|--------------------|--------------|-------|
| 9537 060100 | 7 #24 PVC FS PVC | 100 | 3.7 | CHROME | C |



9537 Non-Paired - Computer Cable for EIA RS-232 Applications

| | | | | | |
|---------------|------------------|-------|------|--------|---|
| 9537 0601000 | 7 #24 PVC FS PVC | 1000 | 30 | CHROME | C |
| 9537 060500 | 7 #24 PVC FS PVC | 500 | 13.5 | CHROME | C |
| 9537 060U1000 | 7 #24 PVC FS PVC | U1000 | 29 | CHROME | |
| 9537 060U500 | 7 #24 PVC FS PVC | U500 | 15 | CHROME | |

C = CRATE REEL PUT-UP.

Revision Number: 1 Revision Date: 05-25-2005

© 2006 Belden Wire & Cable Company
All Rights Reserved.

Although Belden Electronics Division ("Belden") makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden CDT Electronics Division believes this product to be in compliance with the following environmental regulations: California Proposition 65 Consent Judgment For Wire & Cable Mfgs.(San Francisco Superior Court Nos. 312962 And 320342); EU RoHS (Directive 2002/95/EC, 27-Jan-2003);Material manufactured prior to the compliance date may still be in stock at Belden facilities and in our Distributor's inventory. EU ELV (Directive 2000/53/EC, 18-Sept-2000); EU WEEE (Directive 2002/96/EC, 27-Jan-2003); And EU BFR (Directive 2003/11/EC, 6-Feb-2003). The information provided in this Product Disclosure, and the identification of materials listed as reportable or restricted within the Product Disclosure, is correct to the best of Belden's knowledge, information and belief at the date of its publication. The information provided in the Product Disclosure is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.

Belden CDT Electronics Division declares this product to be in compliance with EU LVD (Low Voltage Directive 73/23/EEC), as amended by directive 93/68/EEC.