



1 Modular Terminal Blocks with Fixing Flange or Snap-in Mounting Foot, Series 260


16 Side-entry


0.08 – 1.5 mm² | AWG 28 – 16
 400 V/6 kV/3 ① | 300 V, 10 A ②
 18 A | 300 V, 15 A ③

Terminal block width 5 mm / 0.197 in
 8 – 9 mm / 0.33 in

* 

2 x 0.08 – 1.5 mm² | 2 x AWG 28 – 16
 400 V/6 kV/3 ① | 300 V, 10 A ②
 18 A | 300 V, 15 A ③

Terminal block width 8 mm / 0.315 in
 8 – 9 mm / 0.33 in










* 



① 400 V = rated voltage
 6 kV = rated surge voltage
 3 = pollution degree
 (see also section 10)

Description	Color	Item-No.	Pack.-unit pcs	Color	Item-No.	Pack.-unit pcs
 Terminal blocks with fixing flange , for screw fixing or similar methods, fixing hole diameter 3.2 mm (with mounting adapter 209-123 also for DIN 35 rail)	2-conductor terminal blocks			4-conductor terminal blocks		
	grey	260-301	300 (6 x 50)	grey	260-331	300 (6 x 50)
	light grey	260-303	300 (6 x 50)	light grey	260-333	300 (6 x 50)
	blue	260-304	300 (6 x 50)	blue	260-334	300 (6 x 50)
	orange	260-306	300 (6 x 50)	orange	260-336	300 (6 x 50)
 Terminal blocks with snap-in mounting foot , for plate thickness 0.6 – 1.2 mm, fixing hole diameter 3.5 mm (fits aluminum rail 210-154 or with mounting adapter 209-120 for DIN 35 rail)	2-conductor terminal blocks			4-conductor terminal blocks		
	grey	260-311	300 (6 x 50)	grey	260-341	300 (6 x 50)
	light grey	260-313	300 (6 x 50)	light grey	260-343	300 (6 x 50)
	blue	260-314	300 (6 x 50)	blue	260-344	300 (6 x 50)
	orange	260-316	300 (6 x 50)	orange	260-346	300 (6 x 50)
 End terminal block ③, without fixing foot, for terminal strips with snap-in mounting feet (see dimensioned drawings on page 1.17.)	2-conductor terminal blocks			4-conductor terminal blocks		
	grey	260-321	300 (6 x 50)	grey	260-351	300 (6 x 50)
	light grey	260-323	300 (6 x 50)	light grey	260-353	300 (6 x 50)
	blue	260-324	300 (6 x 50)	blue	260-354	300 (6 x 50)
	orange	260-326	300 (6 x 50)	orange	260-356	300 (6 x 50)
	green-yellow	260-327	300 (6 x 50)	green-yellow	260-357	300 (6 x 50)

Accessories for modular terminal blocks and terminal strips (Marking accessories see section 9.)

 End plate with fixing flange	grey	260-361	100 (2 x 50)	grey	260-361	100 (2 x 50)
 End plate with snap-in mounting foot	grey	260-371	100 (2 x 50)	grey	260-371	100 (2 x 50)
 Comb type jumper bar , insulated, 2-way	I _N 10 A reduce wire to 1 mm ² /AWG 18 max.	260-402	25	I _N 10 A reduce wire to 1 mm ² /AWG 18 max.	260-402	25
 Operating tool , insulated, for connecting the comb type jumper bar	2-way	209-132	1	2-way	209-132	1
 Aluminum carrier rail , 1000 x 18 x 7 mm 3'3" x 0.709 x 0.276 in		210-154	1		210-154	1
 Plastic end stop , with WSB marking facility, for aluminum rail 210-154	6 mm / 0.236 in wide	grey 209-122	25	6 mm / 0.236 in wide	grey 209-122	25
 Mounting adapter , for terminal blocks with snap-in mounting foot, for DIN 35 rail	6 mm / 0.236 in wide	grey 209-120	25	6 mm / 0.236 in wide	grey 209-120	25
 Mounting adapter with screw , for terminal blocks with fixing flange, for DIN 35 rail	6 mm / 0.236 in wide	grey 209-123	25	6 mm / 0.236 in wide	grey 209-123	25
 Mounting adapter for DIN 35 rail , can be used as end stop	6.5 mm / 0.256 in wide	grey 209-137	25	6.5 mm / 0.256 in wide	grey 209-137	25

* For further approvals with corresponding ratings see pages 10.3ff.