

88 KNIPEX-"Alligator", Water Pump Pliers

DIN ISO 8976

- ▶ box-joint design: high stability because of double guide
- ▶ self-locking on pipes and nuts: no slipping on the workpiece; low handforce required
- ▶ guard prevents operators' fingers being pinched
- ▶ favourable lever action: optimum transmission of force
- ▶ gripping surfaces with special hardened teeth, teeth hardness approx. 61 HRC: low wear and secure gripping
- ▶ Chrome Vanadium electric steel, oil-hardened and tempered



88 01 180



88 01 250



88 02 250



88 06 250



88 07 250



Self-locking on pipes and nuts. No slipping on the workpiece and less handforce required



Optimized shape of jaws for gripping pipes and nuts

Article-No.	EAN-Code	Head	Handles	Capacities		g
				for pipes	for nuts	
Length mm	4003773-			○ Inch	⬡ mm (across flats)	
88 00 250	019176	polished	red lacquered	1 1/2	36	300
88 01 180	034445	polished	with non-slip plastic coating	1 1/4	30	185
250	013341			1 1/2	36	315
300	013358			2	46	505
88 02 180	044222	polished	with two-colour	1 1/4	30	215
250	019282		dual component handles	1 1/2	36	355
300	029151			2	46	555
88 03 180	042860	chrome plated	with non-slip plastic coating	1 1/4	30	185
250	005742			1 1/2	36	315
300	019312			2	46	505
88 05 180	060130	chrome plated	with two-colour	1 1/4	30	215
250	035497		dual component handles	1 1/2	36	355
300	042389			2	46	555
88 06 250	039303	chrome plated	insulated with two-colours dual component handles ⚡ 1000 V, VDE-tested	1 1/2	36	370
88 07 250	019343	chrome plated	plastic dipped insulated ⚡ 1000 V, VDE-tested	1 1/2	36	415
300	022350			2	46	635