

Designation:  
UT 4-PE

Short description:

Long description:

Universal terminal block with screw  
connection, cross section: 0.14 - 4 mm<sup>2</sup>, AWG:  
26 - 10, width: 6.2 mm, color: Green-yellow

Technical data:

General:

Conductor cross section, flexible max.:	4 mm <sup>2</sup>
Number of levels:	1
Conductor cross section, rigid max.:	6 mm <sup>2</sup>
Number of connections:	2
Conductor cross section AWG/kcmil max:	10
Color:	green-yellow
Insulating material:	PA
Inflammability class acc. to UL 94:	V0

Dimensions:

Width:	6.2 mm
Length:	46.9 mm
Height NS 35/7,5:	47.5 mm
Height NS 35/15:	55 mm

Technical data:

Rated surge voltage:	8 kV
Contamination class:	3
Surge voltage category:	III
Insulating material group:	I
Connection in acc. with standard:	IEC/ DIN VDE

Connection data:

Conductor cross section, rigid min.:	0.14 mm <sup>2</sup>
Conductor cross section, rigid max.:	6 mm <sup>2</sup>
Conductor cross section flexible min.:	0.5 mm <sup>2</sup>
Conductor cross section, flexible max.:	4 mm <sup>2</sup>
Conductor cross section AWG/kcmil min.:	26
Conductor cross section AWG/kcmil max:	10
Conductor cross section flexible, with ferrule without plastic sleeve min.:	0.25 mm <sup>2</sup>
Conductor cross section flexible, with ferrule without plastic sleeve max.:	4 mm <sup>2</sup>
Conductor cross section flexible, with ferrule with plastic sleeve min.:	0.25 mm <sup>2</sup>
Conductor cross section flexible, with ferrule with plastic sleeve max.:	4 mm <sup>2</sup>
2 conductors with same cross section, solid min.:	0.14 mm <sup>2</sup>
2 conductors with same cross section, solid max.:	1.5 mm <sup>2</sup>
2 conductors with same cross section, flexible, min.:	0.14 mm <sup>2</sup>
2 conductors with same cross section, flexible max.:	1.5 mm <sup>2</sup>
2 conductors with same cross section, flexible, TWIN ferrules with plastic sleeve, min.:	0.5 mm <sup>2</sup>
2 conductors with identical cross section, flexible TWIN ferrules with plastic sleeve, max.:	

3044128\_en

2.5 mm<sup>2</sup>  
2 conductors with same cross section, flexible,  
ferrules without plastic sleeve min.: 0.25 mm<sup>2</sup>  
2 conductors with same cross section, flexible,  
ferrules without plastic sleeve, max.: 1.5 mm<sup>2</sup>  
Type of connection: Screw connection  
Stripping length: 9 mm  
Internal cylindrical gage: A4  
Screw thread: M 3  
Tightening torque, min: 0.6 Nm

Order data:  
Manufacturer: Phoenix Contact  
Type: UT 4-PE  
Order number: 30 44 12 8