

583- 133/145/157/169/



BALANCED MICROPHONE CABLE - DGS 2

Sheet No. **PS 0781**

Date : 06.03.95

Issue No. 1

Sheet 1 of 1

Signature

PRODUCT SPECIFICATION

Deltron Part No. **447-0100 BLACK**
447-0200 BLUE
447-0500 RED
447-0700 YELLOW

Dimensions



- | | |
|----------------------|--------------------------|
| 1 - JACKET | PVC, Ø6,0mm maximum |
| 2 - SHIELD | Copper wires, 0,1mm |
| 3 - FILLING MATERIAL | Viscose |
| 4 - INSULATION | PE, Ø1,5mm |
| 5 - CONDUCTOR | 28 x 0,10mm copper wires |

Description

A balanced microphone cable with single shield, high flexible, velvet faint PVC jacket.

ORDERING DATA

Reels at 100metres (EW250)
 Weight/reel 4,83Kg
 Weight/metre 0,0483Kg
 Colours black, blue, red, yellow

Features

TECHNICAL SPECIFICATION

Conductor Resistance	< 90 Ohms/km
Shield Resistance	< 30 Ohms/km
Insulation Resistance	< 200 Mega Ohms/km
Capacitance	cond/cond : < 125 nF/km cond/shield : < 190 nF/Km
Test Voltage	cond/cond : 500 V eff cond/shield : 1000 V eff
Temperature Range	moved : -5°C to +50°C unmoved : -30°C to +70°C