

- Multi-Tone Sounder in combination with Xenon Flash
- Optical and audible signal can be triggered separately
- Choice of different 8 tones
- Adjustable sound output
- Easy to mount
- High protection rating IP 65



Mounting holes integrated into the product rim allow easy mounting without having to remove the dome.

TECHNICAL SPECIFICATIONS:

Dimensions (Diameter x Height):	89 mm x 100 mm
Housing:	PC, black
Dome:	PC, transparent
Connection:	Screwable connection with wire protection max. 1.5 mm ²
Cable entry:	Membrane cover up to Ø 9 mm
Flash energy:	1 Ws
Flash frequency:	1 Hz
Sound output:	max. 100 dB
Fixing:	Base mounting
Life duration:	4 x 10 ⁶ flashes

ORDER SPECIFICATIONS:

	24 V ≅
red	421 120 75
yellow	421 320 75

Available from September 2005

TONE TYPES AND FREQUENCIES:

Tone A No.	Tone type
1	Horn tone (c. 200 Hz)
2	Continuous (c. 2.3 KHz)
3	1 Hz tone (c.2.3 KHz)
4	20 Hz whistle tone (c. 2.3 KHz)
5	800-970 Hz rising @ 1 Hz
6	2400-2850 Hz rising @ 7 Hz
7	1200-500 Hz falling @ 1 Hz
8	Alternating tone

