

975-795 TO 941

Protector

Protector Series 491	Protector Serie 491	Protector Série 491						
	<p>Limits for pre-arcing time Grenzwerte der Schmelzzeit Temps de fusion limité</p> <table border="1"> <thead> <tr> <th>I/I_{max}</th> <th>t</th> </tr> </thead> <tbody> <tr> <td>100%</td> <td>14.400 s. min</td> </tr> <tr> <td>300%</td> <td>0.1 s. max</td> </tr> </tbody> </table>	I/I _{max}	t	100%	14.400 s. min	300%	0.1 s. max	
I/I _{max}	t							
100%	14.400 s. min							
300%	0.1 s. max							

Packaging: <ul style="list-style-type: none"> per 5000 on reel (EIA standard) for automatic placement per 1000 in Ammo-pack Radial taped type available 	Verpackung: <ul style="list-style-type: none"> pro 5000 in Gürtung (EIA Norme) für automatische Bestückung pro 1000 in Ammo-pack Radial Type in Gürtung lieferbar 	Emballage: <ul style="list-style-type: none"> par bande de 5000 (Norme EIA) pour insertion automatique par 1000 en Ammo-pack Type radial sur bande disponible
---	---	---

Part no. Bestellnr. Références	I _{max} [mA]	U _{max} [V]	RI [Ω]	RI (@ I-max) [Ω]	Pt [A ² s]
491.250	250	60	6.7 × 10 ⁻¹	9.6 × 10 ⁻¹	1.1 × 10 ⁻²
491.315	315	60	5.1 × 10 ⁻¹	7.2 × 10 ⁻¹	2.6 × 10 ⁻²
491.400	400	60	4.0 × 10 ⁻¹	5.3 × 10 ⁻¹	4.0 × 10 ⁻²
491.500	500	60	2.8 × 10 ⁻¹	3.8 × 10 ⁻¹	5.5 × 10 ⁻²
491.630	630	60	2.1 × 10 ⁻¹	2.9 × 10 ⁻¹	1.1 × 10 ⁻¹
491.750	750	60	1.7 × 10 ⁻¹	2.3 × 10 ⁻¹	1.6 × 10 ⁻¹
491.800	800	60	1.6 × 10 ⁻¹	2.3 × 10 ⁻¹	2.2 × 10 ⁻¹
491001.	1000	60	1.2 × 10 ⁻¹	1.9 × 10 ⁻¹	2.8 × 10 ⁻¹
4911.25	1250	60	9.8 × 10 ⁻²	1.6 × 10 ⁻¹	4.7 × 10 ⁻¹
49101.5	1500	60	8.2 × 10 ⁻²	1.4 × 10 ⁻¹	6.5 × 10 ⁻¹
49101.6	1600	60	8.2 × 10 ⁻²	1.3 × 10 ⁻¹	5.4 × 10 ⁻¹
491002.	2000	60	4.7 × 10 ⁻²	7.1 × 10 ⁻²	4.2 × 10 ⁻¹
49102.5	2500	60	3.6 × 10 ⁻²	5.3 × 10 ⁻²	7.2 × 10 ⁻¹
491003.	3000	60	2.9 × 10 ⁻²	4.4 × 10 ⁻²	1.2 × 10 ⁰
4913.15	3150	60	2.9 × 10 ⁻²	4.2 × 10 ⁻²	1.5 × 10 ⁰
49103.5	3500	60	2.4 × 10 ⁻²	3.5 × 10 ⁻²	1.7 × 10 ⁰
491004.	4000	60	2.0 × 10 ⁻²	2.9 × 10 ⁻²	2.4 × 10 ⁰
491005.	5000	60	1.6 × 10 ⁻²	2.2 × 10 ⁻²	3.9 × 10 ⁰